

## Anti-Static Spray

Product Code: ASA

### PRODUCT DESCRIPTION

**Anti-Static Spray** is a very effective cleaner designed to eliminate dust and prevent the build up of static. Specially developed for use in areas where static build-up causes problems, e.g. computer rooms and offices, it is safe for use on plastic, metal, glass and synthetic surfaces. Developed with a "no-stain" formulation, it is suitable for use on fabrics of any colour.

Packaged in a pump spray bottle, **Anti-Static Spray** has been designed for use in workplaces where strict safety regulations prohibit the use of flammable solvents and aerosols, e.g. mines, oil-rigs, submarines and aircraft.

### PRODUCT USE

Spray liberally on surfaces; avoid spraying directly onto live electrical equipment. Reapply at regular intervals and increase use during dry weather conditions.

### FEATURES

- \* Eliminates static discharges and prevents reoccurrence
- \* Prevents damage to voltage sensitive components and circuits
- \* Supplied in pump action bottle for use in hazardous working environments
- \* Safe on delicate surfaces - will not harm plastic surfaces which may be attacked by solvents.

### TYPICAL PROPERTIES


Form:	Colourless liquid with lemon odour
Density:	0.995
pH:	7 to 9
Boiling Point:	>100°C
Flash Point:	Non-Flammable to BAMA Tests

TECHNICAL  
DATA  
SHEET



**Copyright  
Electrolube  
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



## Anti-Static Spray – Page 2

### PACKAGING

250ml Pump spray

### ORDER CODE

ASA250ML

TECHNICAL  
DATA  
SHEET



### **Copyright Electrolube 2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

