













Ø.156 [3,96] 2 PLCS TYP PER POLE R0.347 ^{+0.010} [8,80 ^{+0.25}] ONE PER POLE
1.660 [42,16]
1.050 [26,67]

PANEL CUTOUT DETAIL



A-SERIES CIRCUIT_BREAKER

PROPRIETARY NOTICE
NOTICE TO ALL PERSONS RECEIVING THIS
PRAWING. THIS DOCUMENT IS THE PROPERTY OF
CARLING TECHNOLOGIES, INC. AND IS NOT TO BE
DISCLOSED, REPRODUCED IN WHOLE OR IN
ART OR USED FOR MANUFACTURING PURPOSES
BY ANYONE WITHOUT THE CONSENT OF
CARLING TECHNOLOGIES, INC.

DISCLAIMER

MANUFACTURER RESERVES THE RIGHT TO CHANGE PRODUCT SPECIFICATIONS WITHOUT PRIOR NOTICE.

	DO NOT SCALE DRAWING	;
	UNLESS OTHERWISE SPECIF	FIED
_	DIMENSIONS: IN [MM]	
	TOLERANCES: \pm .020 [0.51	1]
	DRAWING FILE NO.	SIZE
	AA1-B0-34-615-5D1-C	С

PRODUCT SERIES: A-SERIES C.B. | SHEET 1 OF 1

CIRCUIT SCHEMATIC ANSI SERIES TRIP	TABLE A TIGHTENING TORQUE SPECIFICATIONS		[
LINE o	THREAD SIZE	TORQUE	† F
(#6-32 & M3 MOUNTING HARDWARE	7-9- IN-LBS [0.8-1.0 NM]	
	#8-32 & M4 THREAD TERMINAL SCREW	12-15 IN-LBS [1.4-1.7 NM]	MAN PRC
LOAD	#10-32 & M5 THREAD TERMINAL SCREW	15-20 IN-LBS [1.7-2.3 NM]	