21 ± 0.5 16 ± 0.3 $2\times(\phi 5)$ 21 ± 0.5 16 ± 0.3 В В Ø 14. 1 +0. 1 Ø 12.1 +0.2 9 ± 0.5 С 20.5 ± 2 С 3 (11) Caulking Ø 14 ±0.3 Solder cup inside dia.(≠1.1) D D Ε Ε 2 COPPER ALLOY SILVER PLATING 2 m min. DIALLYL PHTHALATE (BLACK) UL94V-0 4 ZINC ALLOY MATTE FINISH NICKEL PLATED 3 DIALLYL PHTHALATE (BLACK) UL94V-0 NO. MATERIAL FINISH REMARKS ΝO MATERIAL FINISH REMARKS REVISIONS DESIGNED CHECKED DATE COUNT DESCRIPTION OF SCALE UNITS F 15. 10. 26 DRAWING NO. APPROVED : HY. KOBAYASHI EDC-027518-00-00 HIROSE ELECTRIC CO..LTD. CHECKED 15. 10. 26 HY. KOBAYASH PART NO. RM12BRB-2PH DESIGNED : HT. ZENBA 15.10.26 CODE NO. CL109-0817-5-00 15. 10. 26 DRAWN ·HT. ZENBA FORM HC0011-5-51

Sep.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved. In case that the application demands a high level of reliability, such as automotive, please contact a company representative for further information.