



TO




CODE No.	PART No.	NUMBER OF CONTACT	A	B	C
CL543-2047-4-27	DF11CZ- 4DP-2V(27)	4	2	8.5	8.7
CL543-2048-7-27	DF11CZ- 6DP-2V(27)	6	4	10.5	10.7
CL543-2049-0-27	DF11CZ- 8DP-2V(27)	8	6	12.5	12.7
CL543-2050-9-27	DF11CZ-10DP-2V(27)	10	8	14.5	14.7
CL543-2051-1-27	DF11CZ-12DP-2V(27)	12	10	16.5	16.7
CL543-2052-4-27	DF11CZ-14DP-2V(27)	14	12	18.5	18.7
CL543-2053-7-27	DF11CZ-16DP-2V(27)	16	14	20.5	20.7
CL543-2054-0-27	DF11CZ-18DP-2V(27)	18	16	22.5	22.7
CL543-2055-2-27	DF11CZ-20DP-2V(27)	20	18	24.5	24.7
CL543-2056-5-27	DF11CZ-22DP-2V(27)	22	20	26.5	26.7
CL543-2057-8-27	DF11CZ-24DP-2V(27)	24	22	28.5	28.7
CL543-2058-0-27	DF11CZ-26DP-2V(27)	26	24	30.5	30.7
CL543-2059-3-27	DF11CZ-28DP-2V(27)	28	26	32.5	32.7
CL543-2060-2-27	DF11CZ-30DP-2V(27)	30	28	34.5	34.7
CL543-2061-5-27	DF11CZ-32DP-2V(27)	32	30	36.5	36.7
CL543-2062-8-27	DF11CZ-40DP-2V(27)	40	38	44.5	44.7




NOTES 1 IF THERE IS PATTERN ON  PART, THERE IS A POSSIBILITY THAT IT WILL MAKE CONTACT WITH THE LEADS.


2 LEAD CO-PLANARITY INCLUDE REINFORCED METAL FITTINGS SHALL BE 0.1mm MAX.

2	BRASS	SURFACE:TIN PLATED 1μm min UNDER PLATING:NICKEL PLATED 0.5μm min	6	POLYESTER	CLEAR(COVER TAPE)
1	POLYAMIDE	UL94V-0, NATURAL (BEIGE)	5	 J	CLEAR(EMBOSSD CARRIER TAPE)
NO.	MATERIAL	FINISH, REMARKS	4	POLYAMIDE	BLACK(ADSORPTIVE CAP)
			3	BRASS	TIN PLATED 1μm min
			NO.	MATERIAL	FINISH, REMARKS
CODE NO. (OLD)			DRAWN	DESIGNED	CHECKED
			A.Miura	N.Hirose	H.Umehara
			'06.04.06	'06.04.06	'06.04.06
					T.Oma
					'06.04.06
DRAWING NO.			PART NO.		
EDC3-307176-02			DF11CZ-*DP-2V(27)		
HRS			CODE NO.		
HIROSE ELECTRIC CO., LTD			CL543-		
 SCALE 5 : 1 UNITS mm			1/2		

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .



PART No.	NUMBER OF CONTACT	D	E	F	G	H	J
DF11CZ- 4DP-2V (27)	4	24.0	—	11.5	13.2	24.4	PS
DF11CZ- 6DP-2V (27)	6	24.0	—	11.5	15.2	24.4	A-PET
DF11CZ- 8DP-2V (27)	8	24.0	—	11.5	17.2	24.4	PS
DF11CZ-10DP-2V (27)	10	32.0	28.4	14.2	19.2	32.4	PS
DF11CZ-12DP-2V (27)	12	32.0	28.4	14.2	21.2	32.4	PS
DF11CZ-14DP-2V (27)	14	44.0	40.4	20.2	23.2	44.4	PS
DF11CZ-16DP-2V (27)	16	44.0	40.4	20.2	25.2	44.4	A-PET
DF11CZ-18DP-2V (27)	18	44.0	40.4	20.2	27.2	44.4	A-PET
DF11CZ-20DP-2V (27)	20	44.0	40.4	20.2	29.2	44.4	PS
DF11CZ-22DP-2V (27)	22	44.0	40.4	20.2	31.2	44.4	PS
DF11CZ-24DP-2V (27)	24	56.0	52.4	26.2	33.2	56.4	PS
DF11CZ-26DP-2V (27)	26	56.0	52.4	26.2	35.2	56.4	A-PET
DF11CZ-28DP-2V (27)	28	56.0	52.4	26.2	37.2	56.4	A-PET
DF11CZ-30DP-2V (27)	30	56.0	52.4	26.2	39.2	56.4	PS
DF11CZ-32DP-2V (27)	32	56.0	52.4	26.2	41.2	56.4	PS
DF11CZ-40DP-2V (27)	40	72.0	68.4	34.2	43.2	72.4	PS



NOTES 3 1 REEL:500 CONNECTORS.

4 AT THE BEGINNING OF THE REEL, 15 COMPONENTS SHALL BE EMPTY.
AT THE END OF THE REEL, 10 COMPONENTS SHALL BE EMPTY.

5 WHEN THE TAPE WIDTH IS 32,44 AND 56mm, SPROCKET HOLES SHALL BE SET ON BOTH SIDES OF REEL AS SHOWN ON THIS DRAWING.


6 THE MATERIAL OF THE EMBOSSED CARRIER TAPE REFERS TO THE TABLE.

7 DETAIL OF PART No. LABEL IS WRITTEN IN JAPANESE.

8 THE REEL IS POLYETHYLENE PACKAGED WITH AN DRY AGENT INSIDE FOR MOISTURE-PROOF PACKAGING.

9 FOR THE STORAGE OF 168 HOURS OR MORE AFTER OPENING THE PACKAGE, KEEP THE PRODUCTS UNDER MOISTURE PROOF CONDITIONS.

10 EXCEPT ON THE MATING SURFACE, COMPONENT INFLATION DOES NOT AFFECT THE PRODUCTS PERFORMANCE.



- SUPPLIER
- QUANTITY
- PART No.
- CODE No.
- DATE OF MANUFACTURED

7) DETAIL OF PART No. LABEL	
生産月日	年 月 日
図 番	CL543-****-*27
品 名	DF11CZ-*DP-2V(27)
納入数量	500 KO
納入者	ヒコセ電機株式会社

CODE NO. (OLD)		DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
		A. Miura '06.04.06	N. Hirose '06.04.06	H. Umehara '06.04.06	T. Oma '06.04.06	
		DRAWING NO.		PART NO.		
SCALE		EDC3-307176-02		DF11CZ-*DP-2V(27)		
FREE		 HIROSE ELECTRIC CO., LTD		CODE NO.		2
UNITS				CL543-		
mm						