


Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case that the application demands a high level of reliability, such as automotive,
please contact a company representative for further information.



NOTE 1 THIS PRODUCT IS ASSEMBLED TO A "DH60-33P".
THE APPLICABLE PANEL THICKNESS IS FROM 1.4 TO 1.6mm.
2 THIS PRODUCT IS PACKED IN A BAG. (QUANTITY IN A BAG : 200pcs.)

1 ASSEMBLED(1:1)

1	STEEL	OVER PLATING : NICKEL 5μm MIN UNDER PLATING : COPPER 1μm MIN	2	STEEL	OVER PLATING : NICKEL 5μm MIN UNDER PLATING : COPPER 1μm MIN
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS
UNITS mm		SCALE 4 : 1	COUNT 2 1	DESCRIPTION OF REVISIONS DIS-E-003059	DESIGNED MO. SHIMOYAMA
HIROSE ELECTRIC CO., LTD.		APPROVED : AO. SUZUKI	09. 04. 27	DRAWING NO. EDC4-126895-00	DATE 09. 12. 07
		CHECKED : MO. SHIMOYAMA	09. 04. 24	PART NO. DH-LNA	
		DESIGNED : TS. ITO	09. 04. 24	CODE NO. CL244-0045-0-00	
		DRAWN : TS. ITO	09. 04. 24		