


RESISTANCE VS TEMPERATURE CHARACTERISTICS:



Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)	Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)
-40	147.10	153.70	160.70	50	1.760	1.796	1.833
-35	108.80	113.40	118.20	55	1.456	1.489	1.522
-30	81.200	84.370	87.650	60	1.211	1.240	1.270
-25	61.050	63.250	65.530	65	1.012	1.039	1.066
-20	46.240	47.770	49.350	70	0.850	0.874	0.898
-15	34.980	36.030	37.120	75	0.717	0.738	0.760
-10	26.690	27.420	28.170	80	0.607	0.626	0.646
-5	20.540	21.040	21.560	85	0.517	0.534	0.552
0	15.920	16.280	16.630	90	0.442	0.458	0.473
5	12.430	12.670	12.910	95	0.380	0.394	0.408
10	9.769	9.936	10.100	100	0.327	0.340	0.352
15	7.736	7.850	7.964	105	0.283	0.294	0.306
20	6.168	6.244	6.321	110	0.246	0.256	0.266
25	4.950	5.000	5.050	115	0.214	0.223	0.232
30	3.980	4.029	4.078	120	0.187	0.195	0.204
35	3.219	3.265	3.312	125	0.164	0.171	0.179
40	2.618	2.661	2.705	130	0.141	0.147	0.154
45	2.141	2.181	2.221	135	0.118	0.123	0.129

NOTES:

1. RESISTANCE @ 25°C :  $5\text{K}\Omega \pm 1\%$ .
2. BETA VALUE (0/50°C) :  $3892\text{K} \pm 1\%$
3. OPERATING TEMPERATURE RANGE : -40°C TO +135°C.
4. DISSIPATION FACTOR :  $1.5\text{mW}/^\circ\text{C}$
5. THERMAL TIME CONSTANT : LESS THAN 3SECONDS IN WATER
- 6.INSULATION RESISTANCE :  $10\text{M}\Omega$  AT 100 VDC

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		<b>molex</b>		
	mm	NTS					
GENERAL TOLERANCES (UNLESS SPECIFIED)	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 657230 DRWN: RAVIKM CHK'D: RBBHASKAR APPR: RBBHASKAR		NTC EPOXY - 3892 40MM 5K1%		
	ANGULAR TOL	± °					
DIVISIONAL SYMBOLS	4 PLACES	±	INITIAL REVISION: DRWN: RAVIKM APPR: RBBHASKAR		PRODUCT CUSTOMER DRAWING		
	3 PLACES	±					
	2 PLACES	±					
	1 PLACE	±					
	0 PLACES	±					
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
			A3-SIZE	215272	2152723505	OTS	1 OF 1