

Feb.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

1			2			3			4		
COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
△					△						

DETAIL OF MOUNTING GUIDE

11 $\pm$ 0.3
8.85 $\pm$ 0.2
14 $\pm$ 0.5
6.3 $\pm$ 0.3
5.1 $\pm$ 0.1
1.6 $\pm$ 0.1
5.1 $\pm$ 0.1
8.1 $\pm$ 0.1
PANEL CUTOUT
t 0.7~2

1
2
3 PRESS FITTING
4 PRESS FITTING
5 ATTACHED
6 ATTACHED

M8 $\times$ 0.5
SOLDER CUP INSIDE DIA. (ϕ 0.8)

NOTE 1 THE RECOMMENDED CLAMP TORQUE OF REF.NO. ⑥ : 1.5N · m .
LOCTITE 242, HENKEL JAPAN OR EQUIVALENT IS RECOMMENDED TO PREVENT
REF. NO. ⑥ FROM LOOSENING.

NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS
3	POLYAMIDE	(BLACK) UL94V-0	6	BRASS	NICKEL PLATING
2	STAINLESS STEEL		5	PHOSPHOR BRONZE	NICKEL PLATING
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED	4	PHOSPHOR BRONZE	SILVER PLATING 2 μ m min.

CODE NO. (OLD)	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
CL ?	D. Matsune '05.09.01	D. Matsune '05.09.01	H. Kishi '05.09.01	M. Sato '05.09.01	

SCALE	DRAWING NO.	PART NO.
2 : 1	EDC4-025302-73	HR10A-7R-5S(73)

UNITS	CODE NO.	
mm	CL110-0320-7-73	1/1

FORM NO.228