










Notes.

1. 100 pcs. / bag
2. The dimensions in parenthesis are reference dimensions.
3. Always refer to the manuals below for operation of this product.
For cable assembly / Cable assembly procedure ETAD-H0760
For mating/unmating / Operation manual ETAD-H0761
For operation / Board-to-Wire Connector Guidelines ETAD-H1023
4. Applicable insulation diameter : $\phi 0.98$ to $\phi 1.2$ mm.
- 5 Although the gate mark on the waterproof wire seal (part No. 2) may be mounted upside down, there is no difference in performance.


Mated figure



DF62WZC-3S-2. 2C



DF62W#-3EP-2. 2C (##)

1	PBT	UL94V-0 (White)		2	Silicone rubber	Gray			
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS			
UNITS mm		SCALE 5 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
									
			APPROVED : S.J. OKAMURA		2024. 12. 25	DRAWING NO.	EDC-403926-00-00		
			CHECKED : HT. SATO		2024. 12. 24	PART NO.	DF62WZC-3S-2. 2C		
			DESIGNED : K.I. SUGAWARA		2024. 12. 24	CODE NO.	CL0544-1108-0-00		
 HIROSE ELECTRIC CO., LTD.	DRAWN : K.I. SUGAWARA		2024. 12. 24						