

e multicomp	PART NO.		REVISIONS							
	2260(5560) - Series	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		-	А	RELEASED	Veena	28/8/08	Suresh	28/8/08	Farnell	12/9/08



Specifications:

•	
Current rating	: 5.0A ac/dc.
Voltage rating	: 250V ac/dc.
Maximum contact resistance	: 10mΩ.
Minimum insulation resistance	: 1000MΩ.
Withstanding voltage	: 1500V ac/minute.
Operating temperature range	: -25°C to +105°C.
Material and Finish:	
Insulator	: High temperature plastic (nylon 66).
Contact	: Phosphor bronze.
Plating	: Tin plated.



Dimensions : Millimetres

believed to be accurate but the Group perioday supplies. The information supplies of believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:				
	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE	Veena	28/08/08	Receptacle				
		CHECKED BY:	DATE:	SIZE DWG NO.		ELECTRONIC FILE	REV	
		Suresh	28/08/08	Δ	M10001612	578565-1578572_DWG	A	
	PURPOSES ONLY.	APPROVED BY:	DATE:					
0	the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC MULTICOMP is the registered trademark of the Group. © Premier Famel plc 2008.		Farnell	12/09/08	SCALE: NTS	U.O.M.: mm	SHEET: 1 OF	F 2


	PART NO.		REVISIONS							
	2260(5560) - Series	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		-	А	RELEASED	Veena	28/8/08	Suresh	28/8/08	Farnell	12/9/08

Specification Table

Number of Positions	А	В	Part Number
8	9.00	12.85	2260(5560)-08
10	12.00	15.85	2260(5560)-10
12	15.00	18.85	2260(5560)-12
14	18.00	21.85	2260(5560)-14
16	21.00	24.85	2260(5560)-16
18	24.00	27.85	2260(5560)-18
20	27.00	30.85	2260(5560)-20

Dimensions : Millimetres

Part Number Explanation:



Number of Positions : 08 = 8, 10, 12, 14, 16, 18 and 20 Positions.

http://www.farnell.com

http://www.newark.com

http://www.cpc.co.uk

believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or or	TOLERANCES: UNLESS OTHERWISE	DRAWN BY: Veena	DATE: 28/08/08	DRAWING TITLE:	Receptacl	e	
	SPECIFIED, DIMENSIONS ARE FOR REFERENCE	CHECKED BY: Suresh	DATE: 28/08/08	SIZE DWG NO.	M10001612	ELECTRONIC FILE 578565-1578572_DWG	REV A
	PURPOSES ONLY.	APPROVED BY: Farnell	DATE: 12/09/08	SCALE: NTS	U.O.M.: mm	SHEET: 2 OF	F 2