

## INSTANT NAILS



Colour	Product Code	Pack Size	Box Qty
White	INST	C3	12
	25INST	C3	25
	EASIINST	C2 Sq	12

### Product Description

EVERBUILD INSTANT NAILS is a high strength solvent free gap filling adhesive that provides a quick “grab” and replaces mechanical fixings in a multitude of Home Improvement applications, both internally and externally. The product has exceptionally quick drying properties for a solvent free adhesive achieving over 50% of its ultimate bond strength in one hour. INSTANT NAILS dries white and is overpaintable when dry.

### Benefits

- Solvent free - environmentally friendly formulation
- Excellent adhesion/bond strength - adheres to most common surfaces -QUICKLY
- Good early grab properties - usable in both vertical and horizontal positions.
- Dries white
- Will adhere to damp surfaces.
- Water clean up - no hazardous solvents.
- Overpaintable.

### Areas For Use

- Sticking wood, metal, PVC , most plastics, glass, aluminium, concrete, render, stone, paper, cork, ceramics plaster/plasterboard, rockwool, Pufoam board, Styrofoam, breezeblock etc
- Bonding dado rails, architrave’s and skirting
- Fixing wall cladding direct to internal wall surfaces or timber battens.
- Fixing battens directly onto walls without fastenings.
- Bonding carpet gripper systems to most floors without the need for nails or tacks.
- Bonding stair nosing to concrete or wooden stairs.
- Securing aluminium or other skin panels to the framework or portable industrial buildings and caravans.

### Limitations

- At least one surface must be porous.
- When used externally, protect from rain until cured.
- In damp, cold or humid conditions, curing time may be significantly extended.
- Do not use in permanently damp/wet conditions.
- Do not in situations where both surfaces are non -porous (eg plastic/plastic - metal/metal) - use GUN A NAIL EXTRA.

- Do not use as a mirror adhesive: use EVERBUILD POLYMER MS.

### Surface Preparation

The surfaces to be glued should be clean and free from dust, grease and other contaminants. Wood, plaster and brick may be damp but not running wet (NOTE This will slow down the drying time). Use mechanical abrasion to clean porous surfaces if necessary before application.

### Application

- Surfaces must be sound, clean, dry and free from dust, grease, loose material etc. At least one surface must be porous.
- Prime dusty surfaces with EVERBUILD PVA BOND diluted 1:4 with water and allow to dry.
- Apply using a standard sealant gun, cut tip of cartridge, apply nozzle and cut an opening to suite the required bead size.
- For bonding heavy items (Plasterboard/worktops/wall panels etc) apply adhesive all the way around the edge of the item (30-50mm from edge) and cover back with beads of adhesive at 300mm intervals. Alternatively, apply adhesive direct to battens and press into place. NOTE.
- *With heavy items, always provide temporary support until the adhesive dries.*
- For bonding lightweight items (covings, dado rails, skirting etc) apply adhesive to back of item in one or two continuous beads and press immediately into place.
- Where gap filling is required, mark the areas where there is a large gap and apply a thicker bead to these areas.
- In all cases, clean up excess adhesive immediately with a damp cloth.

### Specific Data

<b>Form</b>	White thixotropic paste (ready to use)
<b>Viscosity</b>	3000 +/- 1000 cPs (Brookfield Sp70, 10rpm) (low)
<b>Coverage</b>	300ml will cover 11 linear metres (6mm bead)
<b>Solids</b>	75-80%
<b>Cure</b>	Initial: 30 mins. Final: 24-48 hours (dep on substrate)
<b>Specific Gravity</b>	1.44 g/cm <sup>3</sup>
<b>Flash Point</b>	None (solvent free)
<b>Open Time</b>	Max 10 mins at 23°C and 50% R.H
<b>Application Temp</b>	+4 to +35°C
<b>Durability</b>	Up to 15 years when used as recommended

PRODUCT	BOND STRENGTH 30 MINS (N/mm <sup>2</sup> )	BOND STRENGTH 60 MINS (N/mm <sup>2</sup> )	BOND STRENGTH 24 HRS (N/mm <sup>2</sup> )	B.STR (7 days)
Instant Nails	1.22	1.72	2.50	3.3
Leading Brand (solvent free)	Not determined	0.79	2.87	2.83

### Health & Safety

Consult MSDS for full list of hazards.

### Storage

Store in cool dry conditions between + 15°C and 20°C

### Shelf Life

Use within 18 months.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*