FOXElectronics



Farnell Order Code: 1538979 FOX MODEL: FXO-LC535R-212.5 FOX Part Number: 770-212.5-3 LVDS, CERAMIC, SMD, OSCILLATOR

A. Specifications

Parameters			
Frequency	212.5 MHz		
Frequency Stability ¹	±50 PPM		
Temperature Range			
Operating (T _{OPR})	-40°C ~ +85°C		
Storage (T _{STG})	-55°C ~ +125°C		
Supply Voltage (V _{DD})	3.3V ± 5%		
Input Current (IDD)	100 mA Max		
Differential Output Voltage (VoD)	0.250V ~ 0.450V		
Output Offset Voltage (Vos)	1.125V Typ		
Differential Output Swing (V _{P-P})	0.250V _{P-P} Min		
Output Symmetry (50% V _{p-p} Level)	45% ~ 55%		
Rise Time (20% ~ 80% V _{p-p}) (TR)	400 pS Max		
Fall Time (80% ~ 20% V _{p-p}) (TF)	400 pS Max		
Output Load (Recommended Circuit below)	100 ohms		
Startup Time (T _S)	10 ms Max		
Output Enable / Disable Time ²	100 nS Max		
Phase Jitter (12kHz ~ 20MHz)	0.89 pS Typ.		
Maximum Soldering Temp / Time	260°C / 10 Seconds		
Moisture Sensitivity Level (MSL)	1		
Termination Finish	Au		

¹ Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, aging, shock, and vibration.


²An internal pullup resistor from pin 1 to pin 6 allows active output if pin 1 is left open.


ENABLE/DISABLE FUNCTION ²				
Pin 1	OUTPUT (Pin 4, 5)			
OPEN ²	ACTIVE			
'1' Level VIH $\ge 70\%V_{DD}$	ACTIVE			
'0' Level VIL $\leq 30\%V_{DD}$	High Z			

NOTE A 0.01 μ F bypass capacitor should be placed between V _{DD} (Pin6) and GND (Pin 3) to minimize power supply line noise. **RoHS Compliance Status: Compliant**




Drawing is for reference to critical specifications defined by size measurements. Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary







B. Recommended Circuit



NOTE: The above specifications, having been carefully prepared and checked, is believed to be accurate at the time of publication; however, no responsibility is assumed by Fox Electronics for inaccuracies.

Reference / Comments	Title / Description: P	Title / Description: Product Specifications				
	Drawing Number: DV	Drawing Number: DWG-4550-5				
	Part Number: 770-	Part Number: 770-212.5-3 Draftsperson: AR Approved: BN		Cage: 61429		
	Draftsperson: AR			Date: 01/15/2008		
		Page 1 of 1				