



SAFETY DATA SHEET LABELCLENE AEROSOL

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME LABELCLENE AEROSOL
PRODUCT NO. LCL-a
ALCL200
ZA
APPLICATION Cleaning Product
SUPPLIER AF INTERNATIONAL. A division
of HK WENTWORTH LTD
ASHBY PARK
COALFIELD WAY
ASHBY de la ZOUCHE
LEICESTERSHIRE. LE65 1JF
UNITED KINGDOM
+44 (0) 1530 419600
+44 (0) 1530 416640
info@hkw.co.uk
EMERGENCY TELEPHONE +44 (0)1530 419600 between 8.30am - 5.00pm Mon – Fri

2 HAZARDS IDENTIFICATION

Flammable.
Irritating to skin.
May cause sensitisation by skin contact.
Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
CLASSIFICATION (1999/45) Xi;R38. R43. N;R50/53. R10.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
d-LIMONENE	227-813-5	5989-27-5	10-30%	R10 R43 Xi;R38 N;R50/53
C11-C15 ISO-ALKANES	292-460-6	90622-58-5	10-30%	Xn;R65. R66.
C9-C12 ISO-ALKANES	292-459-0	90622-57-4	10-30%	Xn;R65. R66,R53.
3-BUTOXYPROPAN-2-OL	225-878-4	5131-66-8	10-30%	Xi;R36/38

The Full Text for all R-Phrases is Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

4 FIRST-AID MEASURES

NOTES TO THE PHYSICIAN

Treat symptomatically

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

Immediately rinse mouth and provide fresh air.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

LABELCLENE AEROSOL

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Provide good ventilation.

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
3-BUTOXYPROPAN-2-OL	SUP	50 ppm				
C11-C15 ISO-ALKANES			1200 mg/m3			
C9-C12 ISO-ALKANES			1200 mg/m3			

ENGINEERING MEASURES

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

In case of inadequate ventilation and work of brief duration, use suitable respiratory equipment.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. DO NOT SMOKE IN WORK AREA!

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol Liquid
COLOUR	Colourless
ODOUR	Characteristic Lemon
VOLATILITY DESCRIPTION	Volatile.
SOLUBILITY	Insoluble in water
BOILING POINT (°C)	>100
RELATIVE DENSITY	0.820 - 0.840 @ 20 °c
VAPOUR PRESSURE	@ 20 °c

LABELCLENE AEROSOL

pH-VALUE, CONC. SOLUTION	5-6
FLASH POINT (°C)	<55 CC (Closed cup).
AUTO IGNITION	> 200
TEMPERATURE (°C)	
FLAMMABILITY LIMIT - LOWER(%)	0.6
FLAMMABILITY LIMIT - UPPER(%)	7.0

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.

11 TOXICOLOGICAL INFORMATION

INHALATION

Vapours may cause headache, fatigue, dizziness and nausea. High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

SKIN CONTACT

Irritating to skin. May cause sensitisation by skin contact. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT

Irritating to eyes.

ROUTE OF ENTRY

Skin and/or eye contact. Inhalation.

Name	3-BUTOXYPROPAN-2-OL
Toxic Dose 1 - LD 50	2612-5500 mg/kg (oral rat)
Name	d-LIMONENE
Toxic Dose 1 - LD 50	>5000 mg/kg (oral rat)

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

Name	3-BUTOXYPROPAN-2-OL
LC 50, 96 Hrs, Fish mg/l	560-1000
EC 50, 48 Hrs, Daphnia, mg/l	>1000
Name	d-LIMONENE
EC 50, 48 Hrs, Daphnia, mg/l	12.3
Mobility	
The product has poor water-solubility.	

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	AEROSOLS
UN NO. ROAD	1950
ADR CLASS NO.	2
ADR CLASS	Class 2: Gases
ADR PACK GROUP	N/A

LABELCLENE AEROSOL

TUNNEL RESTRICTION CODE	(E)
ADR LABEL NO.	2.2
UN NO. SEA	1950
IMDG CLASS	2.2
IMDG PACK GR.	N/A
EMS	F-D, S-U
UN NO. AIR	1950
AIR CLASS	2.2
AIR PACK GR.	N/A

15 REGULATORY INFORMATION

LABELLING



Irritant



Dangerous for the environment

CONTAINS

d-LIMONENE

RISK PHRASES

R10	Flammable.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.
S2	Keep out of the reach of children.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S24	Avoid contact with skin.
S37	Wear suitable gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S57	Use appropriate containment to avoid environmental contamination.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations.

The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

System of specific information relating to Dangerous Preparations. 2001/58/EC.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

LABELCLENE AEROSOL

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Helen O'Reilly

REVISION DATE NOVEMBER 2009

REV. NO./REPL. SDS 6

GENERATED

SDS NO. 10637

RISK PHRASES IN FULL

R10	Flammable.
R65	Harmful: may cause lung damage if swallowed.
R36/38	Irritating to eyes and skin.
R38	Irritating to skin.
R53	May cause long-term adverse effects in the aquatic environment.
R43	May cause sensitisation by skin contact.
R66	Repeated exposure may cause skin dryness or cracking.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.