
# Har. code H05VVH2-F

# Two-Core Oval 300/500V





# **Application:**

Power supply wire, suitable for indoor small electrical instrument, or general in portable tool

# **Construction:**

Conductor:
Material

: Stranded plain annealed copper wire

#### Insulation:

Material	: PVC
Colours	: Blue and brown

#### Sheath:

Material : PVC

# **Physical Properties:**

Operating temperature : -15°C to 70°C

# **Electrical Properties:**

Voltage test	: Core to core : 1,500 V ac / 1 min
Voltage rating	: 300/500 V

# **Specification Table**

Description	Conductor Stranding (mm (mm <sup>2</sup> ))	Insulation Nominal Inner Diameter (mm)	Sheath Nominal Outer Diameter (mm)	Sheath Colour	Minimum Bend Radius (mm)	Nominal DC Resistance (Ω/km)	Current Rating (A)	Part Number
Cable, Flex, 3192Y, White, 1 mm, 100 m	- 32/0.2 (1)	2.5	3.9 × 6.4	Anv	39	19.5	10	3192Y-1MMWHT100M
Cable, Flex, 3192Y, Black, 1 mm, 100 m			2.0 3.9	5.3 ^ 0.4	3.9 ^ 0.4 Ally	39	19.5	10

**Dimensions : Millimetres** 

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Famell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2011.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

