

ANTI FRICTION DRY PTFE LUBRICANT



PRODUCT OVERVIEW

WD-40 Specialist Anti Friction Dry PTFE Lubricant contains PTFE which provides enhanced lubrication, leaving a clear dry film that won't attract dirt, dust or oil. It's quick drying and also great as a mould release agent. This product can be used on metals, plastic and glass.

FEATURES AND BENEFITS

- ⊕ Dual action Smart Straw applicator for wide area and precision spray applications
- ⊕ Ideal to be used on metals, plastic and glass
- ⊕ Enhanced lubrication and protection
- ⊕ Produces a clear dry film that resists dirt, dust and oil
- ⊕ Reduces friction and wear
- ⊕ Advanced formulation works as an effective mould release agent
- ⊕ Excellent resistance to high temperature ranging from -45°C to +260°C

NSF H2 Registered #145371



NARROW SPRAY



WIDE SPRAY

TYPICAL APPLICATIONS

Blades & Drill Bits, Power Tools & Equipment, Door & Window Tracks, Locks & Catches, Conveyors, Rollers, Chains & Cables, Hinges, Thermoplastics, Metal Extrusions.

DIRECTIONS FOR USE

Shake can well. Apply by spraying directly on surface to be lubricated and protected. Dries in seconds.

TECHNICAL DATA

PROPERTY	HIGH PERFORMANCE SILICONE LUBRICANT
Appearance	Slightly cloudy, deep yellow liquid
Odour	pleasant lemon odour
SG	0.71 - 0.74
Discharge rate	0.6 - 1.2 g/s
Temperature range	Effective performance at temperatures from -45°C to +260°C
Solubility	Not miscible with water
NSF category	H2
Flammability	Classed as extremely flammable under current legislation
Compatibility	Suitable for most surfaces, including plastic, metal and glass
Lubrication ASTM D-4172	Scar depth 0.43 mm
Extreme pressure lubrication ASTM 3233	2310 lb
Corrosion protection ASTM B-117	40% at 24h

PACKAGING SPECIFICATIONS

PRODUCT NUMBER	UNIT SIZE	CASE SIZE
44394	400ml	400ml x 12

