


Metallized Polypropylene Film Capacitor Related Document: IEC 60384-16



MAIN APPLICATIONS

Oscillator, timing and LC/RC filter circuits, high frequency coupling/decoupling, sample and hold circuits.

MARKING

Manufacturer's logo/type/C-value/rated voltage/tolerance/date of manufacture

DIELECTRIC

Polypropylene film

ELECTRODES

Vacuum deposited aluminum

COATING

Flame retardant plastic case (UL-class 94 V-0), blue, epoxy resin sealed

CONSTRUCTION

Extended metallized film (refer to general information)

LEADS

Tinned wire

IEC TEST CLASSIFICATION

55/100/56, according to IEC 60068

OPERATING TEMPERATURE RANGE

-55°C to +100°C

CAPACITANCE RANGE

0.01µF to 0.1µF

CAPACITANCE DRIFT

Up to +40°C, < 0.5% for a period of two years

DISSIPATION FACTOR TAN δ

| MEASURED AT | C ≤ 0.1µF |
|----------------|------------------------|
| 1kHz | 0.4 x 10 ⁻³ |
| 10kHz | 0.6 x 10 ⁻³ |
| 100kHz | 4 x 10 ⁻³ |
| Maximum values | |

FEATURES

Product is completely lead (Pb)-free
Product is RoHS-compliant



CAPACITANCE TOLERANCES

± 10% (K), ± 5% (J), ± 2.5% (H), ± 1% (F)



RATED VOLTAGES (U_R)

160 VDC

RoHS
COMPLIANT

PERMISSIBLE AC VOLTAGES (RMS) UP TO 60HZ

100 VAC

TEST VOLTAGE (ELECTRODE/ELECTRODE)

1.6 x U_R for 2 s

INSULATION RESISTANCE

Measured at 100 VDC after one minute
100,000 MΩ minimum value

TEMPERATURE COEFFICIENT

-250°C x 10⁻⁶/°C (typical value)

MAXIMUM PULSE RISE TIME

dv/dt = 390 V/µs

If the maximum pulse voltage is less than the rated voltage, higher dv/dt values can be permitted.

DERATING FOR DC AND AC CATEGORY VOLTAGE U_C

At +85°C: U_C = 1.0 U_R

At +100°C: U_C = 0.7 U_R

SELF INDUCTANCE

~ 6 nH measured with 2mm long leads

PULL TEST ON LEADS

≥ 30 N in direction of leads according to IEC 60068-2-21

DIELECTRIC ABSORPTION

0.05% (typical value) acc. to IEC 60384-1

RELIABILITY

Operational life > 300,000 h

Failure rate < 5 FIT (40°C and 0.5 x U_R)

For further details, please refer to the general information available at www.vishay.com/doc?26033.





| CAPACITANCE | CAPACITANCE CODE | VOLTAGE CODE 16 160 VDC/100 VAC | | |
|---------------|------------------|------------------------------------|------|-----|
| | | W | H | L |
| 0.01 μ F | - 310 | 5.5 | 7.0 | 7.5 |
| 0.015 μ F | - 315 | 5.5 | 7.0 | 7.5 |
| 0.022 μ F | - 322 | 5.5 | 7.0 | 7.5 |
| 0.033 μ F | - 333 | 7.5 | 9.0 | 7.5 |
| 0.047 μ F | - 347 | 7.5 | 9.0 | 7.5 |
| 0.068 μ F | - 368 | 7.5 | 9.0 | 7.5 |
| 0.1 μ F | - 410 | 9.0 | 11.0 | 7.5 |

Further C-values upon request

RECOMMENDED PACKAGING

| LETTER CODE | TYPE OF PACKAGING | HEIGHT (H) (mm) | REEL DIAMETER (mm) | ORDERING CODE EXAMPLES | PCM 5 |
|-------------|-------------------|-----------------|--------------------|------------------------|-------|
| D | AMMO | 16.5 | S* | MKP 1837-322-162-D | X |
| G | AMMO | 18.5 | S* | MKP 1837-322-162-G | X |
| F | REEL | 16.5 | 350 | MKP 1837-322-162-F | X |
| W | REEL | 18.5 | 350 | MKP 1837-322-162-W | X |
| — | BULK | — | — | MKP 1837-322-162 | X |





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.