

Resistors



RESISTORS ■ VITREOUS



VPR

Resistive Element	Power (watts)	Resistive Range (ohms)	Tolerance	Terminal Style	Packaging
Wirewound	VPR5F = 5-8 VPR10F = 10-12 VPR20H = 20	1-25K 0.4-50K 0.4-100K	±5% (±10% below 1 ohm)	Lug and lead	Individually boxed



VK

Wirewound	VK100N = 100 VK160W = 160-175 VK200W = 200-225	1-100K 1-100K 1-100K	±5%	Radial lug	Individually boxed
-----------	--	----------------------------	-----	------------	--------------------



VPA

Wirewound Adjustable	VP10FA = 12 VP25KA = 25 VP50KA = 50	1-10K 1-25K 1-100K	±10%	Radial lug	Individually boxed
----------------------	---	--------------------------	------	------------	--------------------



VC

Wirewound	VC3D = 3-3.25 VC5E = 5-6.50 VC10F = 10-11	0.1-10K 0.1-25K 0.1-50K	±5% (±10% below 1 ohm)	Axial lead	10 per box Tape and reel
-----------	---	-------------------------------	---------------------------	------------	-----------------------------



VP

Wirewound	VP25K = 25 VP50K = 50	1-100K 1-250K	±5%	Radial lug	Individually boxed
-----------	--------------------------	------------------	-----	------------	--------------------



CMC

Wirewound	CMC5 = 5 CMC10 = 10 CMC25 = 25 CMC50 = 50	.1-2.5K .5-5K 1-10K 1-25K	±1%	Chassis mountable axial lug	Individually boxed
-----------	--	------------------------------------	-----	--------------------------------	--------------------



SC/RW

Wirewound	SC1A/RW70U = 1.0 SC3D/RW79U = 3.0 SC5E/RW74U = 5.0	.1-3K .1-10K 1-25K	±1%	Axial lead	10 per box Tape and reel available
-----------	--	--------------------------	-----	------------	---------------------------------------



CR

Style	Resistive Element	Power Rating (watts)	Resistive Range (ohms)	Tolerance
Rheostat	Wirewound	CR12.5 = 12.5 CR25 = 25 CR50 = 50	1-10K 1-10K 1-10K	±10%

Consult factory for specific tapers
Tolerances not included