Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

SAFETY DATA SHEET

Conductive Epoxy - Part A

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

Identification of the substance or mixture

Product name : Conductive Epoxy - Part A

Chemical name : CW2400-A

Synonyms : Conductive Epoxy - Part A

Product type Solid Use of the substance/mixture Adhesives

Company/undertaking identification

Manufacturer : ITW Chemtronics

> 8125 Cobb Center Drive Kennesaw. GA 30152

Tel. 770-424-4888 or toll free 800-645-5244

Distributor

Importer ITW Contamination Control BV

Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands

Email: info@itw-cc.com

Tel: +31 88 1307 400 FAX: +31 88 1307 499

e-mail address of person responsible for this SDS

: askchemtronics@chemtronics.com

(with hours of operation)

Emergency telephone number : Chemtrec - 1-800-424-9300 or collect 703-527-3887

HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi; R36/38

R43 N; R50/53

Human health hazards : Irritating to eyes and skin. May cause sensitisation by skin contact.

Environmental hazards : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

See Section 11 for more detailed information on health effects and symptoms.

COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation : Mixture

Ingredient name	CAS number	%	EC number	Classification
silver reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	_	60 - 90 10 - 25	231-131-3 500-033-5	N; R50 [1] [2] Xi; R36/38 [1] R43 N; R51/53
See Section 16 for the full text of the R-phrases declared above.				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

FIRST AID MEASURES

First-aid measures

Inhalation

: Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Date of issue/Date of : 1/9/2012. 1/6 revision

4. FIRST AID MEASURES

Ingestion

: Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

See Section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: No specific fire or explosion hazard.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is very toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

: Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (section 8). Follow all fire-fighting procedures (section 5). Do not touch or walk through spilt material.

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods for cleaning up

Small spill

 Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor

Large spill

: Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. HANDLING AND STORAGE

Handling

: Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid contact of spilt material and runoff with soil and surface waterways. Wash thoroughly after handling.

Storage

: Keep container tightly closed and sealed until ready for use. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended

: Use original container.

Date of issue/Date of : 1/9/2012. 2/6 revision

Conductive Epoxy - Part A

EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name Occupational exposure limits

silver EU OEL (Europe, 4/2006). Notes: Indicative

Limit value: 0.1 mg/m3 8 hour(s).

Recommended monitoring

procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure

controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Physical state : Solid. [Paste.] Colour : Grey. [Light]

Important health, safety and environmental information

Boiling point : >93.333°C (>200°F)

Melting point : 961.8°C (1763.2°F) This is based on data for the following ingredient: silver.

Flash point : Closed cup: >93.333°C (>200°F). (Setaflash.)

Explosive properties : Not considered to be a product presenting a risk of explosion.

Vapour pressure : <0.01 kPa (<0.1 mm Hg) (at 20°C)

Relative density : 4 (Water = 1)

Partition coefficient: n-

octanol/water

: The product is insoluble in water and octanol.

Evaporation rate (butyl

acetate = 1)

: <1 compared with butyl acetate

10. STABILITY AND REACTIVITY

Stability : Stable under recommended storage and handling conditions (see section 7).

Conditions to avoid : Avoid release to the environment. Refer to special instructions/safety data sheet.

Materials to avoid : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Date of issue/Date of : 1/9/2012. 3/6 revision

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation : No known significant effects or critical hazards.

Ingestion : Irritating to mouth, throat and stomach.

Skin contact : Irritating to skin. May cause sensitisation by skin contact.

Eye contact : Irritating to eyes.

Acute toxicity

Potential chronic health effects

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Mutagenicity **Teratogenicity** : No known significant effects or critical hazards. **Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation : No specific data. Ingestion : No specific data.

Skin : Adverse symptoms may include the following:

irritation redness

Eyes : Adverse symptoms may include the following:

> irritation watering redness

Target organs : Contains material which causes damage to the following organs: eye, lens or cornea.

Contains material which may cause damage to the following organs: mucous

membranes, skin, nose/sinuses.

12. ECOLOGICAL INFORMATION

Environmental effects

: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

A

	environment.			
Aquatic ecotoxicity				
Product/ingredient name silver	Test -	Result Acute EC50 9.2 ppb Fresh water	Species Daphnia - Water flea - Daphnia magna - <24 hours	Exposure 48 hours
	-	Acute EC50 9.5 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <1 days	48 hours
	-	Acute EC50 0.24 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <1 days	48 hours
	-	Acute LC50 0.0062 mg/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 145 mm	96 hours
	-	Acute LC50 15 to 18 ug/L Fresh water	Crustaceans - Water flea - Simocephalus vetulus - <24 hours	48 hours
	-	Acute LC50 14 ug/L Fresh water	Daphnia - Water flea - Daphnia pulex - <24 hours	48 hours
	-	Acute LC50 11 to 14 ug/L Fresh water	Daphnia - Water flea - Ceriodaphnia reticulata - <4 hours	48 hours
	-	Acute LC50 6.42 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
	-	Acute LC50 6.28 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
	-	Acute LC50 6.25 to 7.3 ug/L Fresh	Fish - Fathead minnow -	96 hours

Date of issue/Date of : 1/9/2012. 4/6

revision

12. ECOLOGICAL INFORMATION

	water	Pimephales promelas - <24 hours	
-	Acute LC50 4.7 to 5.62 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 3.42 to 4.05 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 3.12 to 3.73 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 2.76 to 3.33 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 2.38 to 3.04 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 2.13 to 2.93 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 1.5 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <=24 hours	48 hours
-	Chronic NOEC 1.1 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <=24 hours	48 hours

Conclusion/Summary

Biodegradability

Conclusion/Summary : Not available.

Other adverse effects : No known significant effects or critical hazards.

: Not available.

13. DISPOSAL CONSIDERATIONS

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

International transport regulations

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
ADR/RID Class	Not regulated.	-	-	-		-
ADN/ADNR Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-

PG*: Packing group

Date of issue/Date of : 1/9/2012. 5/6 revision

Conductive Epoxy - Part A

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols :



Irritant, Dangerous for the environment

Risk phrases : R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases : S24- Avoid contact with skin.

S2- Keep out of the reach of children.

S46- If swallowed, seek medical advice immediately and show this container or label.

S29- Do not empty into drains.

S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

Contains : reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight \leq 700)

Product use : Classification and labeling have been determined according to EU Directives

67/548/EEC and 1999/45/EC (including amendments) and take into account the

intended product use.Industrial applications

Europe inventory : All components are listed or exempted.

16. OTHER INFORMATION

Full text of R-phrases referred to in sections 2 and

referred to in sections 2 and 3 - Europe

R36/38- Irritating to eyes and skin.

R43- May cause sensitisation by skin contact.

R50- Very toxic to aquatic organisms.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications

referred to in sections 2 and 3 - Europe

: Xi - Irritant

N - Dangerous for the environment

<u>History</u>

Date of printing : 1/9/2012.

Date of issue/Date of : 1/9/2012.

revision

: No previous validation.

Date of previous issue : No Version : 13

Prepared by : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of : 1/9/2012. 6/6

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

SAFETY DATA SHEET

Conductive Epoxy - CW2400-B

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

Identification of the substance or mixture

Product name : Conductive Epoxy - CW2400-B

Chemical name : CW2400-B

Synonyms : Conductive Epoxy - Part B

Product type Solid Use of the substance/mixture Adhesives

Company/undertaking identification

Manufacturer : ITW Chemtronics

> 8125 Cobb Center Drive Kennesaw. GA 30152

Tel. 770-424-4888 or toll free 800-645-5244

Distributor

Importer ITW Contamination Control BV

Saffierlaan 5 VZ-2132 Hoofddorp The Netherlands

Email: info@itw-cc.com

Tel: +31 88 1307 400 FAX: +31 88 1307 499

e-mail address of person responsible for this SDS

: askchemtronics@chemtronics.com

Emergency telephone number : Chemtrec - 1-800-424-9300 or collect 703-527-3887

HAZARDS IDENTIFICATION

(with hours of operation)

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : C; R34

N; R50

Human health hazards : Causes burns. May cause sensitisation by skin contact.

Environmental hazards : Very toxic to aquatic organisms.

See Section 11 for more detailed information on health effects and symptoms.

COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation : Mixture

Ingredient name	CAS number	%	EC number	Classification
silver 2-piperazin-1-ylethylamine	7440-22-4 140-31-8	60 - 90 10 - 25	231-131-3 205-411-0	N; R50 [1] [2] Xn; R21/22 [1] C; R34 R43 R52/53
See Section 16 for the full text of the R-phrases declared above.				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

FIRST AID MEASURES

First-aid measures

Inhalation

: Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or selfcontained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire,

Date of issue/Date of : 1/9/2012. 1/6 revision

FIRST AID MEASURES

symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Ingestion

: Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

: Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

See Section 11 for more detailed information on health effects and symptoms.

FIRE-FIGHTING MEASURES

Extinguishing media

Suitable

- Use an extinguishing agent suitable for the surrounding fire.
- Not suitable
- : None known.

Special exposure hazards

: No specific fire or explosion hazard.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is very toxic to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

ACCIDENTAL RELEASE MEASURES

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods for cleaning up **Small spill**

: Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

2/6

Date of issue/Date of : 1/9/2012.

revision

7. HANDLING AND STORAGE

Handling

Put on appropriate personal protective equipment (see Section 8). Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment.

Storage

: Keep container tightly closed and sealed until ready for use. Use appropriate containment to avoid environmental contamination.

Packaging materials

Recommended: Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name Occupational exposure limits

silver EU OEL (Europe, 4/2006). Notes: Indicative

Limit value: 0.1 mg/m³ 8 hour(s).

Recommended monitoring :

procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Exposure controls

Occupational exposure

controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

: A respirator is not needed under normal and intended conditions of product use.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or

Skin protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance

Physical state : Solid. [Paste.]
Colour : Grey. [Light]

Important health, safety and environmental information

Boiling point : >204.44°C (>400°F)

Melting point : 961.8°C (1763.2°F) This is based on data for the following ingredient: silver.

Flash point : Closed cup: >93.333°C (>200°F). (Setaflash.)

Explosive properties: Not considered to be a product presenting a risk of explosion.

Explosion limits: Lower: 0.9%

Vapour pressure : <0.1 kPa (<1 mm Hg) (at 20°C)

Relative density : 4.1 (Water = 1)

Partition coefficient: n-

octanol/water

: The product is insoluble in water and octanol.

Vapour density : >1 (Air = 1)

10. STABILITY AND REACTIVITY

Stability

: The product is stable.

Conditions to avoid

: Avoid release to the environment. Refer to special instructions/safety data sheet.

Materials to avoid

: No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of : 1/9/2012. 3/6 revision

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

: NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS Inhalation

WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED.

Ingestion : May cause burns to mouth, throat and stomach.

Skin contact : May cause sensitisation by skin contact.

Eye contact : Irritating to eyes.

Acute toxicity

Product/ingredient name Result **Species** Dose **Exposure** 2-piperazin-1-ylethylamine LD50 Dermal Rabbit 880 uL/kg LD50 Oral Rat 2140 uL/kg

Potential chronic health effects

Chronic effects : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. **Teratogenicity** : No known significant effects or critical hazards. **Developmental effects** : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Fertility effects**

Over-exposure signs/symptoms

Inhalation : No specific data.

Ingestion : Adverse symptoms may include the following:

stomach pains

Skin : Adverse symptoms may include the following:

pain or irritation redness

blistering may occur

: Adverse symptoms may include the following: **Eyes**

> pain watering redness

Contains material which causes damage to the following organs: eye, lens or cornea. **Target organs**

Contains material which may cause damage to the following organs: mucous

membranes, skin, nose/sinuses.

12. ECOLOGICAL INFORMATION

Environmental effects	: Very toxic to aquatic organisi	ms.		
Aquatic ecotoxicity				
Product/ingredient name silver	Test -	Result Acute EC50 9.2 ppb Fresh water	Species Daphnia - Water flea - Daphnia magna - <24 hours	Exposure 48 hours
	-	Acute EC50 9.5 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <1 days	48 hours
	-	Acute EC50 0.24 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <1 days	48 hours
	-	Acute LC50 0.0062 mg/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 145 mm	96 hours
	-	Acute LC50 15 to 18 ug/L Fresh water	Crustaceans - Water flea - Simocephalus vetulus - <24 hours	48 hours
	-	Acute LC50 14 ug/L Fresh water	Daphnia - Water flea - Daphnia pulex - <24 hours	48 hours
	-	Acute LC50 11 to 14 ug/L Fresh water	Daphnia - Water flea - Ceriodaphnia reticulata - <4 hours	48 hours
	-	Acute LC50 6.42 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
	-	Acute LC50 6.28	Fish - Fathead	96 hours

Date of issue/Date of : 1/9/2012. 4/6 revision

ug/L Fresh water

minnow -

12. ECOLOGICAL INFORMATION

		Pimephales promelas - <24 hours	
-	Acute LC50 6.25 to 7.3 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 4.7 to 5.62 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 3.42 to 4.05 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 3.12 to 3.73 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 2.76 to 3.33 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 2.38 to 3.04 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 2.13 to 2.93 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <24 hours	96 hours
-	Acute LC50 1.5 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <=24 hours	48 hours
-	Chronic NOEC 1.1 ug/L Fresh water	Daphnia - Water flea - Daphnia magna - <=24 hours	48 hours
-	Acute LC50 2190000 to 2460000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - 31 days - 21 mm - 0.147 g	96 hours

Conclusion/Summary

2-piperazin-1-ylethylamine

Biodegradability

Conclusion/Summary

: Not available.

: Not available.

Other adverse effects : No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

14. TRANSPORT INFORMATION

International transport regulations

Date of issue/Date of : 1/9/2012. 5/6

14. TRANSPORT INFORMATION

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
ADR/RID Class	Not regulated.	-	-	-		-
ADN/ADNR Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA Class	Not regulated.	-	-	-		-

PG*: Packing group

15. REGULATORY INFORMATION

EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols



Corrosive, Dangerous for the environment

Risk phrases : R34- Causes burns.

R43- May cause sensitisation by skin contact.

R50- Very toxic to aquatic organisms.

Safety phrases : S26- In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S36/37/39- Wear suitable protective clothing, gloves and eye/face protection. S45- In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

Contains : 2-piperazin-1-ylethylamine

Product use : Classification and labeling have been determined according to EU Directives

67/548/EEC and 1999/45/EC (including amendments) and take into account the

intended product use.Industrial applications

Europe inventory : All components are listed or exempted.

16. OTHER INFORMATION

Full text of R-phrases referred to in sections 2 and

3 - Europe

: R21/22- Harmful in contact with skin and if swallowed.

R34- Causes burns.

R43- May cause sensitisation by skin contact.

R50- Very toxic to aquatic organisms.

R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Full text of classifications referred to in sections 2 and

3 - Europe

: C - Corrosive Xn - Harmful

N - Dangerous for the environment

History

Date of printing
Date of issue/Date of

revision

1/9/2012.1/9/2012.

Date of previous issue : No previous validation.

Version : 11

Prepared by : Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue/Date of : 1/9/2012. 6/6