SP Series Industrial Strength Surge Suppression Model SP-6TVN for Home or Office with True Active Tracking® Filter Technology



There are many sources for low-energy transients or "dirty power" that cause disruption and equipment failure. But there's only one real power quality solution and its Active Tracking® Filtering Technology from Emerson Network Power.

The difference between the SP-6TVN and other surge suppression devices is how surge suppression combines with our Active Tracking® Filtering to eliminate electrical abnormalities generated by other equipment located within your home or office. It also eliminates low-voltage transients missed by typical surge suppression technology.

The SP-6TVN is an industrial-strength surge suppression/filtering device that plugs into a standard duplex receptacle. It features uniquely designed repositionable outlets for easy installation behind desks and other furniture. It protects your sensitive home or office equipment, including TVs, home theaters, satellite dishes, computers, printers, copiers and fax machines, from damaging power disturbances traveling through your wiring into your electrical outlets.

Standard Features:

- Plugs into standard 120V, 15AMP electrical outlet
- Total peak surge current capacity of 39,000AMPS
- Cables for telephone, video, and data connections
- Repositionable outlets rotate to accommodate available space
- Perfect for tight spaces, behind furniture and appliances
- Intelligent monitoring against improper wiring/grounding
- 60dB maximum high frequency
- Operational indicator lamp
- 5-year limited warranty
- UL 1449 Listed



SP-6TVN Specifications

| | | AC Power Protection | |
|---|---|---------------------------------|-------------------|
| Nominal Operating Voltage | 120 VAC, Single Phase | | |
| Operating Voltage Range | 120 VAC +/- 10% | | |
| Operating Frequency Range | 47 – 63 Hz | | |
| Rated Output (Amps) | 15 Amperes | | |
| ANSI/IEEE C62.41 Category | Category A & B | | |
| Connection Type | (6) 5- 15R Receptacles and 5- 15P Plug | | |
| Phase Configuration | 2 Wire + Gnd | | |
| Size | 7.5 x 4.75 x 1.75 (Inches) | | |
| Enclosure | High Impact Plastic | | |
| Weight | 2.0 lbs. (0.9 kgs.) | | |
| Modes Of Protection | L – N, L – G, N – G | | |
| Indication of Suppression Status | Status Indicator | | |
| Response Time | < .5 ns Normal mode | | |
| Certifications | UL 1449 Listed | | |
| Warranty | 5 Year | | |
| Maximum Continuous Operating Voltage (MCOV) | | | MCOV) |
| Line to Neutral | 130 VAC | | |
| | Peak Surge Current (8 x 20ms) | | |
| Line to Neutral | 13,000 Amps | | |
| Line to Ground | 13,000 Amps | | |
| Neutral to Ground | 13,000 Amps | | |
| Total | 39,000 Amps | | |
| | ANSI/IEEE C62 | .41 Cat A Ringwave (6 kV, 200A, | , 100 kHz) |
| Normal Mode | 265 V | | |
| Common Mode | 290 V | | |
| | ANSI/IEEE C62.41 Cat B Ringwave (6 kV, 500A, 100 kHz) | | |
| Normal Mode | 275 V | | |
| Common Mode | 290 V | | |
| | Frequency Response | | |
| Normal Mode | 60 dB Maximum, forward/reverse, 100 kHz to 50 MHz | | |
| Common Mode | 40 dB Maximum, forward/reverse, 5 MHz to 50 MHz | | |
| Low Voltage Protection | Video 1 & 2 | Phone | Network |
| Connection Type | Type "F" | Type RJ11 | Type RJ45 |
| Cables Provided | 6' (2x) Type "F" ends | 6' RJ11 Male Ends | 6' RJ45 Male Ends |
| Peak Surge Current | 5kA (8x20us) | 2kA (10x1000us) | 3kA (8x20us) |
| Capacitance | <12pf | <50pf | <70pf |
| Protection Level | L-G | T-R, T-G, R-G | L-G (8 Lines) |
| Clamping Voltage (DC) | 145V | 270-350V | 30V |
| Attenuation | 1db @ 2Ghz | N/A | N/A |



The SP-6TVN is a high-quality surge suppression/filtering device that plugs into a standard duplex receptacle. This uniquely designed product contains repositionable outlets for easier installation behind desks and other furniture. The SP-6TVN protects your sensitive home or office equipment, including TVs, home theaters, satellite dishes, computers, printers, copiers, and fax machines, from damaging power disturbances traveling through your wiring and into your electrical outlets.

Headquarters

Surge and Signal Protection 328 Water Street Binghamton, NY 13901 T: 607-724-2484

T: 800-288-6169

F: 607-722-8713

1805 N.E. 19th Avenue Ocala, FL 34470

T: 352-732-3029 T: 800-648-4076

F: 352-867-1237

23123 E. Mission Ave. Liberty Lake, WA 99019 T: 509-777-2300

T: 800-953-3701

F: 509-927-0435

Technical Support

800 288 6169 Toll-Free 607 724 2484 Phone 607 722 8713 Fax

While every precaution has been taken to ensure accuracy and completeness in this literature, Emerson Network Power assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

All names referred to are trademarks or registered trademarks

SL-22100 (05/06) Printed in USA

Emerson Network Power.

The global leader in enabling Business-Critical Continuity.

- AC Power Systems
- Connectivity
- DC Power Systems
- Embedded Power
- Integrated Cabinet Solutions
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Services
- Site Monitoring
- Surge & Signal Protection

Emerson Network Power.com

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co. ©2006 Emerson Electric Co.