



16 AWG (26 / 0.254 mm) Tinned Copper

Heat Resisting PVC Insulated

Features :

MCTR 161626 Series

T AND THE ACT YW-1 LIANS OF THE A BOUG

Specifications:

Conductors

Insulation

PVC compound meeting the requirements of class 43 PVC		
Minimum Thickness at Any One Point	: 0.34 mm	
Minimum Average Thickness	: 0.38 mm	
Nominal Overall Diameter	: 2.34 mm	
Lay up	: Not Applicable	
Screen	: Not Applicable	
Sheath	: Not Applicable	

Part Number Table

Description	Part Number
Wire, Black, 26 / 30 AWG, 305 m	MCTR 161626 BLK-305M
Wire, Red, 26 / 30 AWG, 305 m	MCTR 161626 RED-305M
Wire, Green / Yellow, 26 / 30 AWG, 305 m	MCTR 161626 G/Y-305M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Famell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage raising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

