Twisted Multipair Cables

pro-**Power**

Screened





Specifications Table

Conductor CSA (mm ²)	0.22					
Core - Core Capacitance (pF / m)	98					
Core - Screen Capacitance (pF / m)	164					
Conductor Make-up	7 / 0.203					
External Diameter	5.71	5.97	6.73	7.24	7.49	10.16
Impedance	77 R					85 R
Conductor Material	Tinned Copper					
Primary Insulation Material	PVC					
Secondary Insulation Material	PVC					
Secondary Insulation Colour	Grey					
Number of Pairs	2	3	4	5	6	15
Number of Cores	4	6	8	10	12	30
Drain Wire Type	Integral					
Primary Screen Type	Aluminised Polyester Tape					
Part Number	PD1002	PD1003	PD1004	PD1005	PD1006	PD1015

Dimensions : Millimetres

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Famell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the Group. © Premier Farnell plc 2012.

