
Telephone Cable



Modular Flat Telephone Cable



Description

Stranded TACW, 4 core, PVC insulation, PVC sheath

Application

Telephone handset cord or line cord

Construction

Conductor Material Stranding	: Stranded TACW : 7 / 0.15 mm
Insulation Material Nominal Inner Diameter Colour	: PVC : 0.95 mm : A : White, B : Green, C : Blue and D : Red
Sheath Material Nominal Outer Diameter Colour	: PVC : 2.9 × 5 mm : Grey
Physical Properties Minimum Bend Radius Operating Temperature	: 29 mm : -15°C to 70°C
Electrical Properties Nominal DC Resistance Voltage Test	: 166 Ω / km : Core to core : 1,000 V ac / 1 minute

Part Number Table

Description	Part Number
Cable, CW1311, 4 Core, 100 m	TEM0037-2009

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Famell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

