Cable and Wires

MCTR 201607 Series



Specifications:

Conductors

20 AWG (7 / 0.32 mm) tinned annealed copper bunch		
Minimum Cross-Sectional Area	: 0.509 mm ²	
Maximum Lay of Bunch	: 31.8 mm	

Insulation

Sheath

PVC compound meeting the requirements	s of class 43 PVC
Minimum Thickness at any One Point	: 0.34 mm
Minimum Average Thickness	: 0.38 mm
Nominal Overall Diameter	: 1.75 mm
Lay Up	: Not Applicable
Screen	: Not Applicable

:	Not	App	olica	ble

Part Number Table

Description	Part Number
Wire, Black, 7 / 28 AWG, 100 m	MCTR 201607 BLK-305M
Wire, Red, 7 / 28 AWG, 100 m	MCTR 201607 RED
Wire, Blue, 7 / 28 AWG, 305 m	MCTR 201607 BLU-305M
Wire, Red, 7 / 28 AWG, 305 m	MCTR 201607 RED-305M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Famell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the Group. © Premier Farnell plc 2012.



www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

Features:

- 20 AWG (7 / 0.32 mm) tinned copper
- Heat resisting PVC Insulated