Switch - DPST





Specifications:

Circut/Function : DPST/ON-OFF

SPST/ON-OFF

DPST/Momentary ON-OFF SPST/Momentary ON-OFF DPST/ON-OFF, illuminated SPST/ON-OFF, illuminated

Terminal Type : 4.8mm× 0.8mm quick connect solder tail

 $\begin{array}{lll} \mbox{Contact Gap} & : \geq 3 \mbox{mm} \\ \mbox{Insulation Spacing} & : \geq 8 \mbox{mm} \\ \mbox{Contact Resistance } (\mbox{m}\Omega) & : < 20 \mbox{ Initially} \\ \mbox{Dielectric Strength (kV)} & : \mbox{Up to } 3.5 \\ \end{array}$

Insulation Resistance (M Ω) : > 50 (500V DC between the Open Contacts) Initially

Endurance

Mechanical Life : ≥ 100,000 Cycles

Electrical Life : ≥ 20,000 Cycles at Full Load

Panel Cut-out

Minimum Panel Thickness : 1mm

Cut-out Size : 19.3mm × 13mm

Maximum Panel Thickness : 3mm

Cut-out Size : 19.5mm × 13mm

Operating Force (N)

Maximum Double-Pole : 10 Maximum Single-Pole : 7

Material

Button/ Body : Nylon 6/6
Iluminated Button : Polycarbonate
Terminals : Copper Alloy
Contacts : Silver Alloy

Soldering Parameters

Soldering Iron Wattage : 50W
Tip Temperature : 300°C

Soldering time : Within 3 Seconds in Off Position

Part Number Table

Description	Part Number
Switch, DPST Mom Black	MC3310-031-01

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



