Lithium Battery Button Cell





Specifications:

Battery Capacity

(on continuous discharge at 20°C

under 30kW load to 2V end-voltage)

Battery Voltage Battery Technology : Lithium **Battery Terminals** : Flat Top Continuous standard load : 30KΩ Weight : 1.3g Battery IEC Code : CR1620 Standard Discharge Current : 0.2mA


: -20°C to +70°C Usable Temp. Range Storage Temp. Range : 0°C to +30°C Storage Humidity Range : 40% to 75% Outer Dimensions : ø16mm (+0 / -0.3)

2mm (+0 / -0.2) (Dia. Overall Height)


Terminals

Cap Terminal : SUS430+Ni-Plated Case Terminal : SUS430+Ni-Plated


Discharge Characteristic




Temperature Characteristic



Load vs. Operating voltage




Load vs. Capacity




Lithium Battery Button Cell




Pulse discharge characteristic




Storage characteristic



Storage at 60 ± for 30 days equivalent to storage at room temperature for 18 months





Dimension: Millimetres

Part Number Table

Description	Part Number
Button, Lithium, 3V, 70mAh	CR1620

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

