Grommet, Sealing







Specifications:

Accessory Type : Grommet
Grommet Type : Cable Retention

Body Material : TPR (Thermoplastic Rubber)

Colour : Black

Physical Property:

www.cpc.co.uk

Hardness +/-5 (Shore A) : 55
Minimum Tensile Strength (Mpa) : 5.2
Minimum Elongation at break (%) : 400

Maximum Compression set (%)

(24 +0/-2 hrs at 70 +/-1 C) : 22

Resistance to accelerated ageing : 168 hours

Change in Hardness (+/-) : 3


Maximum reduction in tensile strength (% of original) : 2

Maximum reduction in elongation at break (%) of : 3

Continuous Operating Temperature : -40°C to +125°C

Grommet, Sealing





Dimensions: Millimetres

Metric			Part Number
Α	В	С	Part Number
12.5	1 - 4	3 - 5	RB 1801
16	1 - 4	5 - 7	RB 1802
19	1 - 4	7 - 10	RB 1803
23	1 - 4	10 - 14	RB 1804
25	1 - 4	10 - 15	RB1806
29	1 - 4	14 - 20	RB 1805

A = Panel Hole

B = Panel Thickness

C = Recommended Cable Size

Part Number Table

Description	Part Number
Grommet, Sealing, 25mm, PK50	RB1806
Grommet, Sealing, 12.5mm, PK50	RB1801
Grommet, Sealing, 16mm, PK50	RB1802
Grommet, Sealing, 19mm, PK50	RB1803
Grommet, Sealing, 23mm, PK50	RB1804
Grommet, Sealing, 29mm, PK50	RB1805

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

