

Dual Temperature Heat Gun

DURATOOL



Features:

- 2 airflow settings with heat and selectable cool air stage for maximum user control
- Also has a soft grip handle for comfortable operation

Specifications:

Heat Temperature Range	: 1050°F
Safety	: Double insulated for safe operation
Cord	: 6½ ft heavy duty industrial grade rubber
Output	: 1,400W
Voltage	: 120V AC / 60Hz
Air Pressure	: 1,079 pA / 0.157 PSI
CFM	: 8½ up to 14.8 ft ³ /min
Circuitry	: State-of-the-art interconnect block circuitry
Switch	: Fully enclosed slide switch
Element Construction	: Reinforced mica composite with ceramic disk
Element Life	: 500h+
Weight	: 1.25 lb
Body Material	: Valax
Dimension	: 3.5" Depth 12.5" Width 9.75" Height
Colour	: Black

Part Number Table

Description	Part Number
Variable Temperature Heat Gun	SPC20538

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2012.

DURATOOL