# **Spray Adhesive**





## Features:

- · This is a fast acting multi-purpose spray adhesive
- · Formulated to provide permanent bonds between a wide variety of materials

## Specifications:

Adhesive Type : Adhesive
Dispensing Method : Can
Chemical Colour : Clear
Volume : 500ml

Adhesive Applications : Bonding / General Purpose

## **Applications:**

Suitable for bonding a wide variety of different materials together including carpet, felt, cloth, slate, wood, metal, plastic, rubber, paper and cardboard. It has been formulated without the use of chlorinated solvents and 'tacks' in approximately 30 - 60 seconds to provide a quick solution to bonding.

## **Directions:**

Apply a light, fine even coating to both surfaces to be bonded from a distance of 25 - 30cm. On porous surfaces apply two coats of adhesive before bonding. Wait until the adhesive is tack-dry and bond the surfaces together using firm pressure.

#### Note:

May affect certain plastics. Not suitable for use on PVC. Always test a small, inconspicuous area before general use. To prevent blockages, invert the can after use and spray to clear the nozzle.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk



# **Spray Adhesive**



### **Technical Information**

Appearance	Clear, amber liquid
Odour	Solvent
SG at 25°C	0.66
Pressure at 25°C	4 Bar
Discharge rate	1.2g/second
Polymer type	Styrene butadiene rubber
Tack time	Approximately 30 - 60 seconds
Bonding time	Maximum adhesion in 12/24 hours
Temperature range	Up to 50°C (dried film)
Flammability	Classified as extremely flammable under CHIP regulations

## Storage:

The product may be stored at normal temperatures and has a shelf life of not less than 36 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flames.

# **Part Number Table**

Description	Part Number
Adhesive Spray, 500ml, Aerosol	PPC105

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

