

## PHXX SERIES 5-25W, AC-DC CONVERTER

PH--- are high efficiency green power modules with various packaging provided by PowerPax. The features of this series are: wide input voltage DC and AC all in one, high efficiency, high reliability, low loss, safety isolation etc. They are widely used in industrial, office and civil equipments. EMC and safety standards meet international standards IEC61000 UL60950 and IEC60950, and Multi-certificate is in processing.




### PRODUCT FEATURES

1. Universal Input :85 ~ 264VAC,50/60Hz
2. AC and DC all in one (input from the same terminal)
3. Low Ripple and Noise
4. Overload protection and short circuit protection
5. High efficiency, High power density
6. Low loss, green power
7. Multiple models available
8. industrial level specifications
9. 3 years warranty

### MODEL SELECTION

#### PH10-10B24



### PRODUCT PROGRAM

Approval	Model	Package	Power	Output (Vo1/Io1)	Output (Vo2/Io2)	Ripple and Noise (Typ.)	Efficiency (%) (Typ.)
UL/CE	PH05-10B03	48.5X36X20.5mm	4W	3.3V/1250mA		50mV	70
UL/CE	PH05-10B05			5V/1000mA			75
UL/CE	PH05-10B09			9V/550mA			77
UL/CE	PH05-10B12			12V/420mA			79
UL/CE	PH05-10B15			15V/330mA			80
UL/CE	PH05-10B24			24V/230mA			82
	PH05-10A05		5W	+5V/500mA	-5V/500mA		75
	PH05-10A12			+12V/210mA	-12V/210mA		79
	PH05-10A15			+15V/160mA	-15V/160mA		79
	PH05-10A24			+24V/100mA	-24V/100mA		80
	PH05-10C0505-01			5V/800mA	±5V/100mA		72
	PH05-10C0512-01			5V/600mA	±12V/100mA		73
	PH05-10C0515-01			5V/600mA	±15V/80mA		74
	PH05-10C0524-01			5V/600mA	±24V/50mA		75
	PH05-10D0505-01			5V/900mA	5V/100mA		73
	PH05-10D0512-01			5V/750mA	12V/100mA		73
	PH05-10D0515-01			5V/700mA	15V/100mA		73
	PH05-10D0524-01			5V/600mA	24V/100mA		75
UL/CE	PH10-10B03	55X45X21.0mm	6.6W	3.3V/2000mA		50mV	70
UL/CE	PH10-10B05			5V/2000mA			76
UL/CE	PH10-10B09			9V/1100mA			78
UL/CE	PH10-10B12			12V/900mA			80
UL/CE	PH10-10B15			15V/700mA			81
UL/CE	PH10-10B24			24V/450mA			82
UL/CE	PH10-10A05		10W	+5V/1000mA	-5V/1000mA		76
UL/CE	PH10-10A12			+12V/450mA	-12V/450mA		80
UL/CE	PH10-10A15			+15V/350mA	-15V/350mA		81
UL/CE	PH10-10A24			+24V/200mA	-24V/200mA		84
	PH10-10C0505-04*			5V/1200mA	±5V/400mA		74
	PH10-10C0512-02			5V/1000mA	±12V/200mA		75
	PH10-10C0515-02			5V/900mA	±15V/200mA		75
	PH10-10C0524-01*			5V/1000mA	±24V/100mA		77
UL/CE	PH10-10D0505-02			5V/1800mA	5V/200mA	50mV	75
UL/CE	PH10-10D0512-02			5V/1500mA	12V/200mA		79
UL/CE	PH10-10D0515-02			5V/1400mA	15V/200mA		79
UL/CE	PH10-10D0524-02			5V/1000mA	24V/200mA		81

Approval	Model	Package	Power	Output (Vo1/Io1)	Output (Vo2/Io2)	Ripple and Noise (Typ.)	Efficiency (%) (Typ.)
UL/CE	PH15-10B03	62x45x22.5mm	9.9W	3.3V/3000mA		50mV	73
UL/CE	PH15-10B05		15W	5V/2800mA			76
UL/CE	PH15-10B09			9V/1600mA			78
UL/CE	PH15-10B12			12V/1250mA			80
UL/CE	PH15-10B15			15V/1000mA			80
UL/CE	PH15-10B24			24V/625mA			84
UL/CE	PH15-10B48			48V/320mA			85
	PH15-10A05			+5V/1500mA	-5V/1500mA		76
	PH15-10A12			+12V/650mA	-12V/650mA		81
	PH15-10A15			+15V/500mA	-15V/500mA		83
	PH15-10C0505-05			5V/2000mA	±5V/500mA		75
	PH15-10C0512-02			5V/2000mA	±12V/200mA		77
	PH15-10C0515-02			5V/1800mA	±15V/200mA		78
	PH15-10C0524-01*			5V/2000mA	±24V/100mA		79
	PH15-10D0505-08			5V/2200mA	5V/800mA		76
	PH15-10D0512-04			5V/2000mA	12V/400mA		80
	PH15-10D0515-03*			5V/2000mA	15V/300mA		80
	PH15-10D0524-02			5V/2000mA	24V/200mA		81
UL/CE	PH20-10B03	70x48x23.5mm	20W	3.3V/4100mA		50mV	73
UL/CE	PH20-10B05			5V/3500mA			75
UL/CE	PH20-10B12			12V/1600mA			81
UL/CE	PH20-10B15			15V/1300mA			83
UL/CE	PH20-10B24			24V/850mA			85
	PH20-10A05			+5V/2000mA	-5V/2000mA		75
	PH20-10A12			+12V/830mA	-12V/830mA		82
	PH20-10A15			+15V/650mA	-15V/650mA		83
	PH20-10C0505-05*			5V/2500mA	±5V/500mA		73
	PH20-10C0512-04			5V/2000mA	±12V/400mA		75
	PH20-10C0515-03			5V/2000mA	±15V/300mA		76
	PH20-10C0524-02			5V/2000mA	±24V/200mA		77
	PH20-10D0505-10*			5V/3000mA	5V/1000mA		73
	PH20-10D0512-06			5V/2500mA	12V/600mA		75
	PH20-10D0515-05*			5V/2500mA	15V/500mA		76
	PH20-10D0524-03			5V/2500mA	24V/300mA		77
UL/CE	PH25-10B05	70x48x23.5mm	25W	5V/4100mA		50mV	74
UL/CE	PH25-10B12			12V/2100mA			82
UL/CE	PH25-10B15			15V/1600mA			83
UL/CE	PH25-10B24			24V/1100mA			85
UL/CE	PH25-10B48			48V/500mA			87

Remarks :

1. Ripple and Noise were measured by the method of parallel lines;
2. Unless otherwise specified, all specifications above are measured at rated input voltage and rated output load, Ta=25°C, humidity < 75%;
3. All specifications stated in this datasheet are subject to the above listed models only. For specifications of non-standard models, please contact our technical support team.
4. Model numbers marked with "." are in developing.


INPUT SPECIFICATIONS			
Input voltage range		85 ~ 264VAC, 120 ~ 370VDC	
Input frequency		47 ~ 63Hz	
Input current	PH05 models PH10 models PH15 models PH20 models PH25 models	110VAC 120mA , typ 230mA , typ 250mA , typ 330mA , typ 420mA , typ	230VAC 70mA , typ 120mA , typ 140mA , typ 180mA , typ 230mA , typ
Inrush current	PH05 models PH10 models PH15 models PH20/PH25 models	110VAC 10A, typ 10A, typ 10A, typ 16A, typ	230VAC 20A, typ 20A, typ 20A, typ 30A, typ
External input fuse(recommended)	PH05 models PH10/PH15 models PH20/PH25 models	1A/250V 2A/250V 3.15A/250V	slow blow slow blow slow blow

OUTPUT SPECIFICATIONS		
Voltage set accuracy		±2% (main output)
Input variation		±0.5% (main output) ±1.5% (supplement output)
Load variation (10-100%)	Single output models Dual output models (balanced load) Isolated triple output (balanced load)  Isolated and separated twin output (balanced load)	±1% ±2% Vo1 ±3% (main output) ±Vo2 ±5% (supplement output) Vo1 ±3% (main output) Vo2 ±5% (supplement output)
Minimum load	single output models Dual output models Isolated and separated twin output Isolated triple output	0% 10% (main output) 10% (main output) 10% (main output)
Ripple & noise(p-p)	20MHz Bandwidth	≤100mV (main output)
Short circuit protection		Continuous, and auto resume
Over current protection		≥110% I <sub>O</sub>
Over output voltage protection	3.3 / 5VDC models 9VDC models 12 / 15VDC models 24VDC models 48VDC models	≤6.5VDC ≤12VDC ≤20VDC ≤30VDC ≤60VDC


COMMON SPECIFICATIONS		
Temperature ranges	Operating : Power derating LH20-10B05     above 55°C: above 50°C:	-25°C ~ +70 °C 3.75% / °C 2.25% / °C Storage: Case temperature: -25°C ~ +105 °C +90°C max
Hold-up time	(Vin=230VAC)	80ms(typ)
Humidity (non condensing)		85%(max)
Temperature coefficient		0.02%/°C (main output) 0.15%/°C (supplement output)
Switching frequency		150kHz    max
Efficiency		78% typ
I/O-isolation voltage		3000VAC/1Min
Leakage current		0.3mA   RMS typ. 230VAC/50Hz
EMI/RFI conducted		EN55022, level B
EMC compliance	Electrostatic discharge ESD RF field susceptibility Electrical fast transients/bursts on mainsline Surge	IEC/EN 61000-4-2 level 3    6KV/8KV IEC/EN 61000-4-3 IEC/EN 61000-4-4 level 3    2KV IEC/EN 61000-4-5 level 3    1KV / 2KV
Safety standards		IEC60950, EN60950, UL60950
Safety approvals		EN60950, IEC60950, UL60950
Safety Class		CLASS 1 (CLASS 2 While LH15)
Case material		UL 94V-0
Install		PCB
MTBF		>200,000h @25°C

## TYPICAL APPLICATIONS


PH\*\*-10B\*\*( Single Output)




PH\*\*-10D\*\*(Isolate Twin Output)



PH\*\*-10A\*\*(Dual Output)



PH\*\*-10C\*\*(Triple Output)



EXTERNAL CAPACITORS TYPICAL VALUE(Unit: mF)


MODEL	C1	C3	C5
PH05-10B03	330		
PH05-10B05	330		
PH05-10B09	120		
PH05-10B12	120		
PH05-10B15	68		
PH05-10B24	68		
PH05-10A05	120	120	
PH05-10A12	68	68	
PH05-10A15	47	47	
PH05-10A24	10	10	
PH05-10C0505-01	220	22	22
PH05-10C0512-01	120	22	22
PH05-10C0515-01	120	22	22
PH05-10C0524-01	120	22	22
PH05-10D0505-01	220	22	
PH05-10D0512-01	220	22	
PH05-10D0515-01	120	22	
PH05-10D0524-01	120	22	
PH10-10B03	470		
PH10-10B05	330		
PH10-10B09	120		
PH10-10B12	120		
PH10-10B15	120		
PH10-10B24	68		
PH10-10A05	220	220	
PH10-10A12	120	120	
PH10-10A15	47	47	
PH10-10A24	33	33	
PH10-10C0505-04	220	120	120
PH10-10C0512-02	220	68	68
PH10-10C0515-02	220	47	47
PH10-10C0524-01	220	47	47
PH10-10D0505-02	220	68	
PH10-10D0512-02	220	68	
PH10-10D0515-02	220	47	
PH10-10D0524-02	220	47	

MODEL	C1	C3	C5
PH15-10B03	680		
PH15-10B05	680		
PH15-10B09	470		
PH15-10B12	220		
PH15-10B15	220		
PH15-10B24	68		
PH15-10B48	33		
PH15-10A05	470	470	
PH15-10A12	220	220	
PH15-10A15	120	120	
PH15-10C0505-05	470	220	220
PH15-10C0512-02	470	120	120
PH15-10C0515-02	470	120	120
PH15-10C0524-01	470	47	47
PH15-10D0505-08	470	470	
PH15-10D0512-04	470	220	
PH15-10D0515-03	470	120	
PH15-10D0524-02	470	47	
PH20-10B03	330		
PH20-10B05	330		
PH20-10B12	220		
PH20-10B15	220		
PH20-10B24	220		
PH20-10A05	470	470	
PH20-10A12	120	120	
PH20-10A15	68	68	
PH20-10C0505-05	330	220	220
PH20-10C0512-04	330	120	120
PH20-10C0515-03	330	120	120
PH20-10C0524-02	330	47	47
PH20-10D0505-10	330	330	
PH20-10D0512-06	330	220	
PH20-10D0515-05	330	220	
PH20-10D0524-03	330	120	
PH25-10B05	330		
PH25-10B12	330		
PH25-10B15	330		
PH25-10B24	120		
PH25-10B48	68		


**Remark:**

- Output filtering capacitors C1, C2 and C3 are electrolytic capacitors, It is recommended to use high frequency and low impedance electrolytic capacitors. For capacitance and current of capacitor please refer to manufacture's datasheet. Voltage derating of capacitor should be 80% or above. C2,C4,C6 are use to filter high frequency noise. TVS is recommended component to protect post-circuits (when converter fails).
- External input NTC is recommended to use 5D-9 ( Only PH10 models and PH15 models)

## TYPICAL EFFICIENCY CURVE




## INPUT VOLTAGE VS LOAD




\*Note: When input DC,  $V_{dc}=1.414V_{ac}-20V_{dc}$ .

## TEMPERATURE VS LOAD




## PARALLEL LINES MEASURE



## TRIM APPLICATION & TRIM CALCULATION

**Application circuit for TRIM**  
(Part in broken line is the interior of models)



**Formula for resistance of Trim**


$$\begin{aligned} \text{up: } R_T &= \frac{aR_2}{R_2-a} - R_3 & a &= \frac{V_{ref}}{V_{ot}-V_{ref}} \cdot R_1 \\ \text{down: } R_T &= \frac{aR_1}{R_1-a} - R_3 & a &= \frac{V_{ot}-V_{ref}}{V_{ref}} \cdot R_2 \end{aligned}$$

Note: Value for R1, R2, R3, and Vref refer to the following table.  
 $R_T$ : Resistance of Trim

a: User-defined parameter, no actual meanings.

Vo(V)	3.3	5	12	15	24	48
Resistance						
R1(KΩ)	2	3.3	3.83	7.5	8.66	1.2
R2(KΩ)	1.2	3.3	1	1.5	1	22
R3(KΩ)	1	1	1	1	1	1.2
Vref(V)	1.24	2.5	2.5	2.5	2.5	2.5
Vot(V)	Output voltage of Trim, variation $\leq \pm 10\%$					

## OUTLINE AND DIMENSIONS



Note:  
Unit: mm  
Pin section: 1.00mm  
Pin length(H):  $\geq 6.00$ mm  
Pin tolerances:  $\pm 0.1$ mm  
General tolerances:  $\pm 0.5$ mm

First Angle Projection

### OUTLINE AND DIMENSIONS

NO.	PH05	PH10	PH15	PH20	PH25
A	12.5	17.5	17.5	20.0	20.0
B	48.5	55.0	62.0	70.0	70.0
C	40.5	47.0	54.0	62.0	62.0
D	4.0	5.0	5.0	5.75	5.75
E	16.0	20.0	20.0	23.0	23.0
F	36.0	45.0	45.0	48.0	48.0
G	20.5	21.0	22.5	23.5	23.5
I	4.0	4.0	4.0	4.0	4.0

### FOOTPRINT DETAILS



Pin	PHXX-10B	PHXX-10A	PHXX-10C	PHXX-10D
1				
2	AC(N)	AC(N)	AC(N)	AC(N)
3	AC(L)	AC(L)	AC(L)	AC(L)
4	-Vo	-Vo	-Vo1	-Vo1
5	No Pin	No Pin	+Vo1	+Vo1
6	No Pin	COM	-Vo2	No Pin
7	No Pin	No Pin	COM	-Vo2
8	+Vo	+Vo	+Vo2	+Vo2
Trim	Trim**	No Pin	No Pin	No Pin

There is no pin "1" on PH15-10BXX  
Trim\*\*: Only fo PH20/25-10BXX series.

### MODELS WEIGHT

WEIGHT	PH05	PH10	PH15	PH20	PH25
(Typ.)	50g	70g	80g	120g	120g

## PACKAGE DIAGRAM



Package box: L\*W\*H=355\*192\*93mm

Package quantity: 20pcs (PH05 series: 40pcs)

# AC-DC Converter Application Guidelines

## 1. Foreword

The following guidelines should be carefully read prior to converter use. Improper use may result in the risk of electric shock, damaging the converter, or fire.

### 1. 1 Risk of Injury

- A. To avoid the risk of burns, do not touch the heat sink or the converter's case.
- B. Do not touch the input terminals or open the case and touch internal components, which could result in electric shock or burns.
- C. When the converter is in operation, keep hands and face at a distance to avoid potential injury during improper operation.

### 1. 2 Installation Advice

- A. Please make sure the input terminals and signal terminals are properly connected in accordance with the stated datasheet requirements.
- B. To ensure safe operation and meet safety standard requirements, install a **slow blow** fuse at input of the converter.
- C. Installation and use of AC/DC converters should be handled by a qualified professional.
- D. AC/DC converters are used in the primary transmission stage of a design and thus, should be installed in compliance with certain safety standards.
- E. Please ensure that the input and output of the converter are incorporated into the design out of the reach of the end user. The end product manufacturer should also ensure that the converter is protected from being shorted by any service engineer or any metal filings.
- F. The application circuits and parameters shown are for reference only. All parameters and circuits are to be verified before completing the circuit design.
- G. These guidelines are subject to change without notice; please check our website for updates.

## 2. General AC-DC Converter Applications

### 2.1 Basic Application Circuit




Figure 1. General AC-DC converter applications circuit

In Figure 1, F1 refers to the input fuse. Proper fuse selection should be a safety agency approved, slow blow fuse. Selection of the proper fuse rating is necessary to ensure power converter and system protection (potential failure if the rating is too high) and prevent false fuse blowing (which could happen if the rating is too low). Below is the formula to calculate the proper rating:

$$I = 3 \times V_{o1} \times I_{o1} / \eta / V_{in(min.)}$$

$V_{o1}$  = output voltage

$I_{o1}$  = output current;

$\eta$  = the converter's efficiency;

$V_{in(min)}$  = the minimum input voltage

Further circuit notations:

- ♦ **NTC** is a thermistor.
- ♦ **CY** and **CX** are safety capacitors.
- ♦ **C1** is a high frequency ceramic capacitor or polyester capacitor, 0.1 $\mu$ F/50V.
- ♦ **C2** is output filtering high frequency aluminum electrolytic capacitor. Select a 220 $\mu$ F rating if the output current is greater than 5A, or a 100 $\mu$ F rating if the output current is less than 5A. The insulation voltage should be derated to less than 80% of rated value.

For dual or triple output converters, the circuit of input side remains the same and the outputs should be considered independently in component selection (see Figure 3).

The application circuit shown in Figure 1 is typical application circuit, whereby all PowerPax products will meet EMI Class B, and Class 3 lightning strike and surge testing (see component datasheets for more details). To comply with more stringent EMC testing, additional filtering should be incorporated. See Figure 2 for a suggested filtering circuit.




Figure 2. Input filter circuit




Figure 3. Typical application circuit



For multi-output converters, the main output is typically a fully regulated output. If the end application requires critical regulation on the auxiliary output(s), a linear regulator or other regular should be added after the converter. (Note: Some PowerPax converters have built in linear regulators; please contact our Technical Department for details).

### **3. AC-DC Converter Safety Related Design Notes**

#### **3.1 Marking Requirements**

Wherever, there are fuses, protective grounds, or switches, clear symbols should be indicated according safety standards. Touchable dangerous high voltage and energy sources should be marked with “**Caution!**” indications.

#### **3.2 Input Cable Requirements:**

Input cables of L, N and E should be brown, blue and yellow/green cables, respectively. Ensure that the ground cable (yellow & green cable) of Type I devices (those that rely on basic insulation and protection ground to avoid electric shock) are securely connected to the ground, and the earth resistance is lower than  $0.1\Omega$

#### **3.3 Clearance and Creepage**

For Type I devices, ensure:

- ◆ L and N are in front of the fuse.
- ◆ The clearance distance between the input and the metal case is above 2mm and creepage is above 2.5mm.

For Type II devices (those that rely on strengthened insulation or double insulation to avoid electric shock) ensure:

- ◆ L and N are in front of the fuse
- ◆ The clearance distance between the input and the metal case is above 2mm and creepage is above 2.5mm.
- ◆ The clearance between the input and the metal case or SELV is above 4mm, and creepage of that is above 5mm.

#### **3.4 Input energy**

If the input capacitor is large, a discharge resistor may be added to ensure that, after disconnect, the voltage held between Input L, N, and the protective ground will be discharged to 37% of its maximum value or below. In Figure 2, R1 is the discharge resistor.

### **4. Heat Dissipation in AC/DC Converter Module Applications**

Trends toward higher density in AC/DC module designs make heat dissipation an important concern. The effect of heat on the electrolytic capacitor is of particular concern, as the life of such capacitors can be drastically reduced when operated in a constant high temperature environment, leading to a higher potential for failure. Proper handling of heat will increase the life of the converter and surrounding components, thus lowering risk of failures. Some

suggestions for handling dissipated heat are summarized, below:

### (1) Ambient Air Cooling

For miniature and high power density converters, free air cooling is recommended, mainly due to cost and space concerns.

- ◆ Heat dissipates to the ambient air through the converter case or exposed surfaces. Heat may also dissipate to ambient air if there is a gap between the converter and the PCB.
- ◆ Heat dissipates from the converter case and exposed surfaces to PCB by radiation.
- ◆ Heat conducts through terminals (pins) to PCB.




Figure 4. converter assembled on PCB

In such applications, please pay particular attention to:

- A. Air Flow - Because the heat dissipation is mainly through convection and radiation, the converter needs an environment with good air flow. It may be helpful to design heat dissipation venting holes throughout the end product, near the converter's location. For best convection cooling, ensure that air flow is not blocked by large components
- B. Layout of Heat Generating Components - In most applications, the AC/DC converter is usually not the only heat generating component. It is recommended to keep a good distance between each heat generating component to minimize heat dissipating clusters.
- C. PCB Design - The PCB, which the power converter is assembled on, is not only a base to mount the converter, but also acts as a heat sink for it, therefore heat dissipation should be considered in PCB layout. We recommend extended the area of the main copper loop and decrease the component density on the PCB to improve the ambient environment.

### (2) Heat Sinks

When free air convection is not sufficient enough, we recommend the use of a heat sink for further cooling. As the converters are filled with heat conductive silicon or epoxy, the heat distribution in converter is even and it radiates from the converter to the air. The efficiency of this convection is dependent on the size of the surface area of the converter. The use of heat sinks is a practical method to add surface area and improve the convection. There are many kinds of heat sinks available in the market. PowerPax recommends considering the following factors in selecting a heat sink:

- ◆ The heat sink should be made of a good heat conducting material, such as aluminum and copper.
- ◆ The larger the surface area, the better the radiation. Therefore, heat sinks usually have a ridged surface or special coatings to make a larger surface area.
- ◆ Use the longest and thickest possible heat sink for best convection.

Heat sinks are best attached to the converter's surface, where the difference in temperature between the surface and the ambient is largest. The use of heat conductive material between the heat sink and the converter's surface to make a better contact and to improve heat conductance is suggested. To avoid case distortion, please do not affix the heat sink too firmly to the converter case.


### (3) Forced Air Cooling

In some systems, where a heat sink does not effectively reduce the ambient temperature, a fan is used to improve the heat radiation. Fans can lower the surface temperature of the converter, but large fans also occupy extra space in the system. It is important to select a suitable fan size, where the speed of the fan will determines how effective it is. The faster the speed, the better the effect on reducing radiated heat. As high speed will also cause increased noise, there is a need to balance the choice between the how effective the fan is against how much audible noise it generates.

A long, rectangular shaped AC/DC converter should use a horizontal fan, and channeled heat sinks should use vertical fans, in order to encourage air flow through the channels.

## 5. Input Under Voltage Impact

### 5.1 Block Diagram of AC/DC Converter




### 5.2 Impact to Converter Reliability

The input voltage range of PowerPax's AC/DC converters is 85~264VAC or 120~370VDC. When the converter is operated within the rated input voltage range, the output current can be used up to the maximum rated specification. The total output power is  $I_o \times V_o$ .

If the converter is operated with an input voltage that is under the rated voltage, offering the same output power of  $I_o \times V_o$ , causes the current ( $I_s$ ) at the transistor (S) to be increased. Long term operation under this condition will damage the transistor (S).

### 5.3 Input Voltage vs Load Capability (PD03-00B24)



Load	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	110%	120%	130%	140%
85VAC	23.85	23.82	23.79	23.77	23.74	23.71	23.68	23.65	23.61	23.58	23.57	23.19	19.2	14.7	11
80VAC	23.83	23.82	23.82	23.83	23.82	23.82	23.81	23.81	23.81	23.8	21	18.5	15	13	10.5
75VAC	23.83	23.83	23.83	23.83	23.82	23.82	23.82	23.81	23.77	20.29	16.65	14.02	10.98	9.39	7.04
70VAC	23.83	23.83	23.83	23.83	23.82	23.82	23.81	23.79	19.96	16.44	13.32	11.14	8.79		
65VAC	23.83	23.83	23.83	23.83	23.82	23.82	23.82	23.8	19.6	15.67	12.46	9.57	7.65		
60VAC	23.83	23.83	23.83	23.83	23.82	23.51	17.86	14.13	10.52	8.28	0				