

XIAMETER(R) SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.1
Revision Date: 18.02.2013
Superseded date: 07.10.2011

DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

1.1 Product name : DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

1.2 Identified uses : Adhesive, binding agents

Uses advised against : None known.

1.3 Company : Dow Corning Europe S.A.
rue Jules Bordet - Parc Industriel - Zone C
B-7180 Seneffe
Belgium

E-mail address (Safety Data Sheet) : sdseu@dowcorning.com

Customer Service : English Tel: +49 611237507
Français Tel: +32 64511149

Fax: +49 611237601
Fax: +32 64888683

1.4 Emergency Phone Number : Dow Corning (Barry U.K. 24h) Tel: +44 1446732350
Dow Corning (Wiesbaden 24h) Tel: +49 61122158
Dow Corning (Seneffe 24h) Tel: +32 64 888240

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to EU Directives 67/548/EEC or 1999/45/EC:

Not hazardous.

2.2 Label elements

Labelling according to EEC Directive

S-phrases : S24 Avoid contact with skin.
S51 Use only in well-ventilated areas.

2.3 Other hazards

Vapours may form explosive mixtures with air.

XIAMETER(R) SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.1
Revision Date: 18.02.2013
Superseded date: 07.10.2011

DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone elastomer

According to EU Directives 67/548/EEC or 1999/45/EC:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
Silicon dioxide	112945-52-5	601-216-3	-	7.1	Substance with a Community workplace exposure limit
Methyltriacetoxysilane	4253-34-3	224-221-9	-	2.0	R14 R34 Xn R22

According to Regulation (EC) No. 1272/2008:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
Silicon dioxide	112945-52-5	601-216-3	-	7.1	Substance with a Community workplace exposure limit
Methyltriacetoxysilane	4253-34-3	224-221-9	-	2.0	Acute toxicity (Oral): Category 4 - H302 Skin corrosion/irritation: Category 1C - H314 EUH014

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

4. FIRST AID MEASURES

4.1 Description of First Aid Measures:

- On contact with eyes** : Flush with water.
- On skin contact** : Flush with water.
- If inhaled** : Remove to fresh air.
- On ingestion** : No first aid should be needed.

XIAMETER(R) SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.1
Revision Date: 18.02.2013
Superseded date: 07.10.2011

DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

5. FIRE-FIGHTING MEASURES

- 5.1 Suitable extinguishing media** : On large fires use dry chemical, foam or water spray (fog). On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
- Unsuitable extinguishing media** : None known.
- 5.2 Hazards during fire fighting** : Vapours may form explosive mixtures with air.
- Hazardous Combustion Products** : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.
- 5.3 Special protective equipment/procedures** : A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** : Wear proper protective equipment.
- 6.2 Environmental precautions** : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
- 6.3 Methods and materials for containment and cleaning up** : Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAGE

- 7.1 Advice on safe handling** : General ventilation is required. Local ventilation is recommended. Do not breathe vapour. Do not breathe spray or mist. Avoid skin and eye contact. Do not empty into drains.
- 7.2 Advice on storage** : Do not store with oxidizing agents.
Vapours may form explosive mixtures with air.
Storage temperature: maximum 32 °C
- 7.3 Specific uses** : Refer to technical data sheet available on request.

XIAMETER(R) SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.1
Revision Date: 18.02.2013
Superseded date: 07.10.2011

DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Name	CAS-No.	Exposure Limits
Silicon dioxide	112945-52-5	4 mg/m ³ TWA Respirable dust 10 mg/m ³ TWA Inhalable dust

8.2 Exposure controls

Engineering Controls : Ventilation : Refer to Section 7.1

Personal protection equipment

Respiratory protection : Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.
A suitable respirator must be worn if the product is used in any circumstances where an aerosol or mist may be generated, such as during spraying or similar activities. Depending on the working conditions, wear a respiratory mask with filter(s) EP or use a self-contained respirator.
The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection supplier.

Hand protection : Chemical protective gloves should be worn: Butyl rubber. Nitrile rubber. Neoprene rubber. Silver shield(TM). 4H(TM). Viton(TM). Regarding glove's breakthrough time, contact your chemical protective glove supplier.

Eye/face protection : Face shield or safety goggles.

Skin protection : Wear impervious overalls in circumstances where significant skin contact can occur.

Hygiene measures : Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.

Additional information : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these types of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

Environmental exposure controls : Refer to section 6 and 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Viscous Liquid

XIAMETER(R) SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.1
Revision Date: 18.02.2013
Superseded date: 07.10.2011

DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

Colour	:	Colorless
Odour	:	Acetic acid
Boiling point/range	:	> 100 °C
Flash point	:	87 °C (Closed Cup)
Explosive properties	:	No Vapours may form explosive mixtures with air.
Specific Gravity	:	1.03
Viscosity	:	45,000 mPa s at 25°C.
Oxidizing properties	:	No

The above information is not intended for use in preparing product specifications.

10. STABILITY AND REACTIVITY

10.1 Reactivity	:	None known.
10.2 Stability	:	Stable under normal usage conditions.
10.3 Possibility of hazardous reactions	:	None known.
10.4 Conditions to avoid	:	None established.
10.5 Materials to avoid	:	Can react with strong oxidising agents.
10.6 Hazardous decomposition products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

On contact with eyes	:	Vapour irritates.
On skin contact	:	Slightly irritating.
If inhaled	:	The vapour is irritating to the mouth, nose and throat.
On ingestion	:	Irritant to mucous membranes.

Chronic toxicity:

On skin contact	:	Can irritate on prolonged or repeated skin contact.
------------------------	---	---

**XIAMETER(R)
SAFETY DATA SHEET**

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.1
Revision Date: 18.02.2013
Superseded date: 07.10.2011

DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

If inhaled	:	Prolonged or repeated inhalation may cause irritation of the upper respiratory system.
On ingestion	:	Repeated swallowing may cause gastrointestinal irritation and disturbance.
<u>Toxicokinetics, metabolism and distribution</u>	:	No specific information is available.
<u>Other Health Hazard Information</u>	:	This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form.

¹ Based on product test data.
² Based on test data from similar products.

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

12.2 Persistence and degradability

This product hydrolyses in water or moist air, releasing acetic acid and organosilicons. Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

12.3 Bioaccumulation

No bioaccumulation is predicted.

12.4 Release to waters / Mobility in soil

Fate and effects in waste water treatment plants:

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria are predicted. The siloxanes in this product do not contribute to the BOD.

13. DISPOSAL CONSIDERATIONS

Product and packaging disposal	:	Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
---------------------------------------	---	---

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

Not subject to ADR/RID.

**XIAMETER(R)
SAFETY DATA SHEET**

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.1
Revision Date: 18.02.2013
Superseded date: 07.10.2011

DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Status

EINECS	:	All ingredients listed, exempt or notified (ELINCS).
TSCA	:	All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.
AICS	:	All ingredients listed, exempt or notified.
IECSC	:	All ingredients listed or exempt.
ENCs/ISHL	:	All ingredients listed, exempt or notified.
KECL	:	All ingredients listed, exempt or notified.
PICCS	:	All ingredients listed, exempt or notified.
DSL	:	All ingredients listed or exempt.

XIAMETER(R) SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 1.1
Revision Date: 18.02.2013
Superseded date: 07.10.2011

DOW CORNING(R) 734 FLOWABLE SEALANT, CLEAR

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning supplying entity shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements.

Source of information: Internal data and publically available information

R14 Reacts violently with water., **R22** Harmful if swallowed., **R34** Causes burns.

H302 Harmful if swallowed., **H314** Causes severe skin burns and eye damage.

XIAMETER(R) is a trademark of Dow Corning Corporation

<http://www.xiameter.com>