## Flexible 2 Core Cable Semiconductive Plastic Screen





## **Description:**

Clear and Yellow polyethylene insulated 30/0.12mm (0.35mm²) tinned copper conductors laid with 30/0.12mm tinned copper drain wire in a semiconductive plastic bedding giving a high level of screening with no degradation due to cable/screen movement. Sheathed overall in Type 8 Arctic grade PVC for high flexibility.

## **Specifications:**

Reel Length : 100m No. of Conductors : 2

No. of Strands x Strand Size : 30 x 0.12mm
Conductor Area CSA : 0.35mm²
Jacket Colour : Blue

Jacket Material : PVC (Polyvinyl Chloride)

Secondary Insulation Material : Arctic Grade PVC

External Diameter : 6.6mm

Conductor Material : Copper

Core - Core Capacitance : 91pF

Core-Screen Capacitance : 178pF

## **Part Number Table**

Description	Part Number
Cable, Screen, 2 Core, Blue, 100m	2/X/449 BLUE 100M

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

