



Features & Benefits

- Cat 6 performance
- Suitable for Gigabit Ethernet
- Ultra-slimline design
- LJ6C style module
- Interchangeable with other LJ6C modules and blanks
- Individually QA tested
- Easy to use shield connection

Specification

Width	25mm
Depth	22mm
Height	38.5mm
Recommended Back-box Depth	32mm
Mounting Hole Size	22mm x 37mm
Panel Thickness	2.0mm max
Material	Polycarbonate/ABS thermoplastic resin with grade UL94 VO at 1.5mm flame retardency
Finish	High gloss
IDC Labels	Colour coded to T568B
Cable Guide	Integrated cable tie position
Sockets	High performance shielded RJ45
IDC Blocks	4 way industry standard IDC blocks
Conforms to	ANSI/TIA-568-C.2 Category 6 Specification

Ordering Information

Product Description	Part Number
CCS Cat 6 FTP Compact LJ6C Module	008-000-001-40
LJ6C Single One Gang Faceplate	008-009-001-00
LJ6C Dual One Gang Faceplate	008-009-002-00
LJ6C Quad Two Gang Faceplate	008-009-004-00
Quad Panel for Ackerman Floorbox	008-011-001-06
LJ6C Blank	008-001-004-07

The Connectix Category 6 FTP LJ6C Module provides the performance needed for present and next generation data communications networks and applications, including Gigabit Ethernet, with the added benefit of shielding to minimise the risk of EMI. The use of next generation components and specially designed boards allow a bandwidth of 250MHz to be achieved in a shielded package.

Connectix LJ6C Modules are ideal for use in floorboxes, or any application that has an industry standard LJ6C aperture. Single and dual gang faceplates are available for up to four LJ6C modules in addition to panels suitable for Ackerman Floorboxes. Their attractive high gloss finish and easy to use labelling system makes them popular with both installers and end users alike. Installation is made easy with the unique colour coded cable saddle and the use of industry standard IDCs.

The modules are fully compliant with the ANSI/TIA Category 6 standards. When used in conjunction with Connectix Category 6 FTP Patch Panels and FTP Cable the user will get a link performance exceeding Category 6 requirements.

