

# "MINI" AUTOMOTIVE FUSE CLIPS & HOLDERS

For .110 (2.8) x .032 (.80) MINI BLADE FUSES


For Littelfuse Mini 297 or 997 series/Bussmann ATM series or equivalent

## VERTICAL FUSE ENTRY


### Thru Hole Mount




- Low Profile



#### Mounting Detail For Two Clips



#### Pad Layout For Two Clips




AVAILABLE ON TAPE AND REEL

### Surface Mount



- Low Profile



CAT. NO. 3563 (Bulk)

CAT. NO. 3563TR (Tape & Reel)


Tape & Reel Spec's: 24mm wide; 12mm pitch; 13 inch reel (1500 pieces per reel)

CAT. NO. 3564





### SPECIFICATIONS

**Material:** .012 (.30) Brass  
**Insulator:** Glass filled Nylon, UL Rated 94V-0  
**Current Rating:** 15 Amps @ 500V AC  
**Temperature Rating:** -58°F to +292°F (-50°C to +145°C)



#### Mounting Detail For Two Clips



CAT. NO. 3544 Tin-Nickel Plate

CAT. NO. 3544-2 Tin Plate




### LOW PROFILE MINI FUSE HOLDER

For Littelfuse Low Profile Mini 897 series or equivalent


- Low insertion force
- Thru hole PC mountable, maintains position during wave soldering
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time

### SPECIFICATIONS

**Contacts:** .016 (.41) Brass, Tin-Nickel Plate  
**Insulator:** Nylon 4/6, UL Rated 94V-0  
**Current Rating:** 20 Amps @ 500V AC  
**Temperature Rating:** -58°F to +292°F (-50°C to +145°C)




#### Mounting Detail




Refer to page 39 for Cat. No. 3557 Clip details

#### Mounting Detail



### MINI FUSE HOLDER

For Littelfuse Mini 297 or 997 series/Bussmann ATM or equivalents



CAT. NO. 3557-2


CAT. NO. 3568

## HORIZONTAL FUSE ENTRY



For Littelfuse Mini 297 or 997 series/Bussmann ATM series or equivalent

### SPECIFICATIONS

**Contacts:** .012 (.30) Brass  
**Insulator:** Nylon 6/6, UL Rated 94V-0  
**Current Rating:** 15 Amps @ 500V AC  
**Temperature Rating:** -58°F to +292°F (-50°C to +145°C)



#### Mounting Detail For Two Clips



CAT. NO. 3549 Nickel Plate

CAT. NO. 3549-2 Tin Plate