PRODUCT SPECIFICATION

Brand
Product Range
Catalogue number
Date

C.K Non-contact voltage detector 2271, 2272 08/02/2013



Range Description

Non-contact voltage detector with visual

Features

Item

Number

T2271

T2272

- Sutable for non-contact AC voltage te earting/ground connection checks, proconnection check, broken wire detect
- High sensitivity tester, offering an external externa contact voltage detection range of 70-
- T2271 Bright red LED illumination of AC voltage
- T2272 Bright red LED illumination & on detection of AC voltage
- Installation category CATIII 1000v off • against transient voltage spikes for th of fixed installations
- Double insulated to ensure safe use • circuitry
- Ergonomic dual component body con handy pocket clip
- On/Off button for longer battery life

audible/visual indicator

Uses 2 x 1.5v AAA batteries (Not sup

scription ct voltage detector with visual indicator			
ble for non-contact AC voltage tests, ng/ground connection checks, proper hection check, broken wire detection a sensitivity tester, offering an extensive non- act voltage detection range of 70-1000v AC 71 - Bright red LED illumination on detection of voltage 72 - Bright red LED illumination & audible alarm etection of AC voltage allation category CATIII 1000v offers protection nst transient voltage spikes for the safe testing ted installations ble insulated to ensure safe use near live itry momic dual component body constructed with dy pocket clip Df button for longer battery life is 2 x 1.5v AAA batteries (Not supplied)		T2271	
Item Description	EAN No	Commodity code	Carton Qty
Non-contact voltage detector with visual indicator	5013969844917	90303399	36
Non-contact voltage detector with audible/visual indicator	5013969844924	90303399	36

Technical product						
information	Specifications	T2271 & T2272				
	Voltage detection range	70-1000v AC				
	Operating temperature	-10 to +50 Degrees C				
	Frequency range	50 to 500Hz				
	Indicator (T2271)	Visual LED indicator				
	Indicator (T2271)	Visual LED indicator & audible alarm				
	Installation category	CAT III				
	Power supply	2 x 1.5v AAA batteries (Not supplied)				
Standards compliance	None applicable					
User health and safety information	None applicable					
RoHS/WEEE compliance	This product range does not fall within the scope of RoHS. The product is WEEE compliant					
Material safety data	None applicable					
Warranty	C.K voltage detectors are guaranteed for 12 months against imperfect materials or workmanship. Damage caused by use outside of the operating instruction guideline is not covered					
Country of origin	China					

Dimensional details

	Product only				Product on primary packaging			
ltem	Width mm	Depth mm	Height mm	Net weight g	Width mm	Depth mm	Height mm	Gross weight g
T2271	23	19	160	18	113	20	208	39
T2272	23	19	165	22	113	20	208	43

	Shelf box (secondary pa	Euro Pallet data Wi x Hi			
ltem	Width mm	Depth mm	Height mm	Gross weight g	No of cartons on base	Number of rows high
T2271	220	460	125	1625	-	-
T2272	220	460	125	1769	-	-

Packaging waste details

	Primary Packaging				Secondary packaging			
Item	Plastic g	Use	Card g	Use	Plastic g	Use	Card g	Use
T2271	10	Blister	11	Backing card	-	-	221	Box
T2272	10	Blister	11	Backing card	-	-	221	Box

Copyright Carl Kammerling International Ltd

Copyright Carl Kammerling International Ltd