CONTROL PRODUCTS

PCB TERMINAL BLOCKS

INTER-CONNECTION

FUSES & FUSE-HOLDERS

LEDs & INDICATORS

MINIATURE SWITCHES

LIMIT & SAFETY SWITCHES

CONTROL PRODUCTS

INTERFACE MODULES & SUPPORTS

RELAY BASES

ENCLOSURES

BATTERIES

TRANS-FORMERS

152

Heavy Duty Footswitch

- Industrial die-cast footswitch Positive opening operation for heavy duty applications
- Snap action and slow action contact blocks 1 NO + 1 NC
- Rising saddle-washer terminal connections
- Single or double-pole contact blocks
- · Silver contacts
- Anti Slip foot pedal
- Non-slip rubber feet
- · Supplied with cable gland
- IP65 Sealed
- (€ approved

SPECIFICATIONS			
Contact Block Rated	10A		
Insulation voltage (Ui)	500VAC 600VDC		
Protection against short circuits	fuse 10A 500V type aM		
Alternate current: AC15 (50-60Hz)			
Ui (V)	250	400	500
Ie (A)	6	4	1
Direct current: DC13			
Ue (V)	24	125	250
Ie (A)	6	1.1	0.4
Connectors flexible wire sizes	min	1 x 0.5 mm ²	(1 x AWG 20)
	max	2 x 2.5mm²	(2 x AWG 14)
Actuating force	single snap action 10N		10N
-	single slow action		12N
	double snap	action	13N
	double slow	action	15N
Ambient temperature	from -25°C to +80°C		
Weight guarded	1.4 kg		
Unquarded	0.55 kg		

Guarded

PART NO.	DESCRIPTION
CFSHC1	Guarded 1 snap action
	contact block
CFSHC2	Guarded 1 slow action
	contact block
CFSHC1C1	Guarded 2 snap
	action contact blocks
CFSHC2C2	Guarded 2 slow
	action contact blocks
CFSHC1C2	Guarded 1 snap and
	1 slow action contact
	blocks



PART NO.	DESCRIPTION
CFUHC1	Unguarded 1 snap action
	contact block
CFUHC2	Unguarded 1 slow action
	contact block
CFUHC1C1	Unguarded 2 snap
	action contact blocks
CFUHC2C2	Unguarded 2 slow
	action contact blocks
CFUHC1C2	Unguarded 1 snap and
	1 slow action contact
	blocks





+44 (0)1638 716101