

ESD Floor Mat Grounding Kit



Specifications:

Mat:

Construction : Dual layer rubber material
Static Dissipative top layer
Conductive rubber bottom layer

Material Thickness : 0.06" ($\pm 10\%$)

Dimensions : 0.078" \times 48" \times 72"

Colour : Dark Blue

Texture : Smooth

Dissipative Colour Side :
RTT: 10E6 - 10E8 Ω per ANSI/ESD S4.1
RTG: 10E6 - 10E8 Ω per ANSI/ESD S4.1

"Slows charge removal; meets minimum recommended work surface requirements of ANSI/ESD S20.20 and recommendations of STM 4.1"

Ground Cord:

Length : 15 ft.
Terminations : 10mm male stud snap, ring terminal
Resistor : 1m Ω

Universal Snap Kit:

Size : 10mm
Kit Includes : 10mm stud snap, 10mm socket snap, threaded backing washer, long screw, short screw and groundable point label.

Packaging:

Product to be packaged with Duratool label

Tolerances:

Width : ± 0.25 "
Length : ± 0.25 " every 1 linear foot of running material

Part Number Table

Description	Part Number
Dark Blue, Dual layer Mat with Domed Ground Cord and Universal snap Kit	MC35757

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2012.

