



ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F005.DWG

REVISIONS

DOC. NO. SPC-F005 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
911	B	Updated	JWM	9/18/00	JC	11/30/00	JC	11/30/00
1385	C	Lid label was KL-5	JWM	11/18/02	JC	11/21/02	JC	11/21/02

Bill Of Material

ITEM	DESCRIPTION	PART NUMBER	QTY
1	Nylon Cable Clamp -- .125 Dia. Cable	NCC-2	50
2	Nylon Cable Clamp -- .250 Dia. Cable	NCC-4	50
3	Nylon Cable Clamp -- .375 Dia. Cable	NCC-6	25
4	Nylon Cable Clamp -- .500 Dia. Cable	NCC-8	25
5	Nylon Cable Clamp -- .750 Dia. Cable	NCC-12	15
6	Nylon Cable Clamp -- 1.0 dia. Cable	NCC-16	10
7	TRANSPARENT STORAGE BOX	8537-0706	1
8	KIT LID LABEL	KL-23N2619	1

8

VOLTREX[®]

NYLON CABLE CLAMP ASSORTMENT
8408-NCC

TYPE NCC NYLON CELLULOSE CABLE CLAMPS

- Anchor tubing, cables, wire bundles, etc.
- Secure quickly with a single nail or screw
- Light weight and chemical resistant
- Excellent shock resisting properties
- Temperature Range -40F to 185F
- Flammability: UL94V-2
- This product absorbs or releases moisture depending on its environment. Moisture level will affect tensile strength, stiffness, and elongation of the product.

TYPE NCC-2	TYPE NCC-4	TYPE NCC-6	TYPE NCC-8	TYPE NCC-12	TYPE NCC-16
CABLE DIA. .125	CABLE DIA. .250	CABLE DIA. .375	CABLE DIA. .500	CABLE DIA. .750	CABLE DIA. 1.000
MTG. DIST. .328	MTG. DIST. .422	MTG. DIST. .484	MTG. DIST. .562	MTG. DIST. .765	MTG. DIST. .908
CLEARANCE NO. 3	CLEARANCE NO. 3	CLEARANCE NO. 3	CLEARANCE NO. 3	CLEARANCE NO. 10	CLEARANCE NO. 10
WIDTH .375	WIDTH .375	WIDTH .375	WIDTH .375	WIDTH .500	WIDTH .500
QTY 50	QTY 50	QTY 25	QTY 25	QTY 15	QTY 10

Important use instructions:
 See Policy in Customer Satisfaction. If any 90% guarantee period does not conform to above conditions, the product will be replaced or refunded. All dimensions are in inch units, and metric units are provided for reference only. Specifications are at final finish, and require proper operation and maintenance. The user shall determine the suitability of the product for the intended use and assume all risk and liability whatsoever in connection therewith. SPC Technology is not responsible for any damage or injury to persons or property, or for any loss of data, or for any other consequences of the use of this product, or for any other consequences of the use of this product.

7

1

2

3

4

5

6

NOTE: KIT LID SHOWN OPEN.

DISCLAIMER:
 ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

TOLERANCES:
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	DATE:
JAP	9/01/92
CHECKED BY:	DATE:
APPROVED BY:	DATE:

DRAWING TITLE: Nylon Cable Clamp Assortment			
SIZE A	DWG. NO. 8408-NCC	ELECTRONIC FILE 23N3619.dwg	REV C
SCALE: NTS	U.O.M.: INCHES [mm]	SHEET: 1 OF 1	