

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 9

sds no.: 179515 V002.4

Revision: 07.07.2011 printing date: 04.12.2013

1 8

Loctite 7649

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier:

Loctite 7649

Relevant identified uses of the substance or mixture and uses advised against:

Intended use:

activator

Details of the supplier of the safety data sheet:

Henkel Limited

2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 Fax-no.: +44 1606 863762

ua-products a fety. uk @uk.henkel.com

Emergency telephone number:

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

Classification of the substance or mixture:

Classification (DPD):

F+ - Extremely flammable

R12 Extremely flammable.

Xi - Irritant

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

MSDS-No.: 179515 Loctite 7649 Page 2 of 9

V002.4

Label elements (DPD):

Xi - Irritant

F+ - Extremely flammable





Risk phrases:

R12 Extremely flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Safety phrases:

S23 Do not breathe vapour.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37 Wear suitable gloves.

S51 Use only in well-ventilated areas.

Additional labeling:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children

For consumer use only: S2 Keep out of the reach of children

S46 If swallowed, seek medical advice immediately and show this container or label.

Other hazards:

The aerosol container is under pressure. Do not expose to high temperatures.

SECTION 3: Composition/information on ingredients

General chemical description:

Activator

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acetone 67-64-1	200-662-2	80- 90 %	Flammable liquids 2 H225 Specific target organ toxicity - single exposure 3 H336 Serious eye irritation 2 H319
Propane 74-98-6	200-827-9	10- 15 %	Flammable gases 1 H220 Gases under pressure

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

MSDS-No.: 179515 Loctite 7649 Page 3 of 9

V002.4

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Acetone 67-64-1	200-662-2	80 - 90 %	R66 Xi - Irritant; R36 F - Highly flammable; R11 R67
Propane 74-98-6	200-827-9	10 - 15 %	F+ - Extremely flammable; R12

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

Description of first aid measures:

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

Most important symptoms and effects, both acute and delayed:

Vapors may cause drowsiness and dizziness.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

SECTION 5: Firefighting measures

Extinguishing media:

Suitable extinguishing media:

Carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

None known

Special hazards arising from the substance or mixture:

None

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

MSDS-No.: 179515 Loctite 7649 Page 4 of 9

V002.4

Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact. Ensure adequate ventilation. See advice in chapter 8

Environmental precautions:

Do not let product enter drains.

Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Chapter 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Use only in well-ventilated areas.

Vapours should be extracted to avoid inhalation.

Keep away from sources of ignition - no smoking.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

Conditions for safe storage, including any incompatibilities:

Store in a cool, well-ventilated place.

Keep away from heat and direct sunlight.

Specific end use(s):

activator

SECTION 8: Exposure controls/personal protection

Control parameters:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m3	Type	Category	Remarks
ACETONE	1.500	3.620	Short Term Exposure		EH40 WEL
67-64-1			Limit (STEL):		
ACETONE	500	1.210	Time Weighted Average		EH40 WEL
67-64-1			(TWA):		
ACETONE	500	1.210	Time Weighted Average	Indicative	ECTLV
67-64-1			(TWA):		
PROPANE				Included in the regulation but	EH40 WEL
74-98-6				with no data values. See	
				regulation for further details	

Exposure controls:

Respiratory protection:

Use only in well-ventilated areas.

Filter type: P2

Hand protection:

The use of chemical resistant gloves such as Neoprene or Natural Rubber are recommended

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

MSDS-No.: 179515 Loctite 7649 Page 5 of 9

V002.4

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties:

Appearance aerosol green

Odor pungent

pH not applicable Initial boiling point $56 \,^{\circ}\text{C} \, (132.8 \,^{\circ}\text{F})$ Flash point $-18 \,^{\circ}\text{C} \, (0.4 \,^{\circ}\text{F})$

Decomposition temperature No data available / Not applicable

Vapour pressure 230 mbar

(20 °C (68 °F))

Density 0,8 g/cm3 (20 °C (68 °F))

Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Miscible

(Solvent: Water)

Solubility (qualitative) Soluble

(Solvent: Acetone)

Solidification temperature

Mo data available / Not applicable

Melting point

No data available / Not applicable

Flammability

No data available / Not applicable

Auto-ignition temperature

No data available / Not applicable

Explosive limits

lower 2,5 %(V) upper 13 %(V)

Partition coefficient: n-octanol/water

Evaporation rate

Vapor density

Oxidising properties

No data available / Not applicable

Other information:

No data available / Not applicable

SECTION 10: Stability and reactivity

Reactivity:

Reacts with strong oxidants.

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

See section reactivity

Conditions to avoid:

Stable

Incompatible materials:

No data available.

Hazardous decomposition products:

Irritating organic vapours.

MSDS-No.: 179515 Loctite 7649 Page 6 of 9

V002.4

SECTION 11: Toxicological information

General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

This material is considered to have low toxicity if swallowed.

Inhalative toxicity:

May cause headache and dizziness.

Skin irritation:

Solvent may remove essential oils from the skin making it susceptible to attack from other chemicals.

Eye irritation:

Irritating to eyes.

Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Acetone	LD50	5.800 mg/kg	oral		rat	
67-64-1	LC50	76 mg/l	inhalation	4 h	rat	
	LD50	> 15.688 mg/kg	dermal		rabbit	

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Acetone	not irritating		rabbit	OECD Guideline 405 (Acute
67-64-1				Eye Irritation / Corrosion)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Acetone	negative	bacterial reverse	with and without		OECD Guideline 471
67-64-1		mutation assay (e.g			(Bacterial Reverse Mutation
		Ames test)			Assay)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Acetone	NOAEL=2500 ppm		13 weeks	rat	
67-64-1		drinking			
		water			

SECTION 12: Ecological information

General ecological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Ecotoxicity:

Do not empty into drains / surface water / ground water.

Mobility:

The product evaporates readily.

Persistence and Biodegradability:

No data available.

MSDS-No.: 179515 Loctite 7649 Page 7 of 9

V002.4

Bioaccumulative potential:

No data available.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
Acetone 67-64-1	LC50	8.120 mg/l	Study Fish	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Acetone 67-64-1	EC50	6.098,4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Persistence and degradability:

Ī	Hazardous components	Result	Route of	Degradability	Method
	CAS-No.		application		
ſ	Acetone	readily biodegradable	aerobic	81 - 92 %	EU Method C.4-E (Determination
	67-64-1				of the "Ready"
					BiodegradabilityClosed Bottle
					Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Acetone	0,24					
67-64-1						

SECTION 13: Disposal considerations

Waste treatment methods:

Product disposal:

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

Disposal must be made according to official regulations.

Waste code

14 06 03 Other solvents and solvent mixtures

SECTION 14: Transport information

Road transport ADR:

Class: 2

Packaging group:

Classification code: 5F

Hazard ident. number:

UN no.: 1950 Label: 2.1

Technical name: AEROSOLS

Tunnelcode: (D)

MSDS-No.: 179515 Loctite 7649 Page 8 of 9

V002.4

Railroad transport RID:

Class: 2

Packaging group:

 Classification code:
 5F

 Hazard ident. number:
 23

 UN no.:
 1950

 Label:
 2.1

Technical name: AEROSOLS

Tunnelcode:

Inland water transport ADN:

Class: 2

Packaging group: Classification code:

Hazard ident. number:

UN no.: 1950 Label: 2.1

Technical name: AEROSOLS

Marine transport IMDG:

Class: 2.1

Packaging group:

UN no.: 1950 Label: 2.1 EmS: F-D ,S-U

Seawater pollutant:

Proper shipping name: AEROSOLS

Air transport IATA:

Class: 2.1

Packaging group:

Packaging instructions (passenger) 203
Packaging instructions (cargo) 203
UN no.: 1950
Label: 2.1

Proper shipping name: Aerosols, flammable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

5F

VOC content 99 %

(1999/13/EC)

MSDS-No.: 179515 Loctite 7649 Page 9 of 9

V002.4

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R11 Highly flammable.

R12 Extremely flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.