Harmony XVU Tower Lights

Customizable and super-bright tower lights for increased visibility of machine status and alarms

The Schneider Electric Harmony™ XVU tower light range offers a clean, innovative design that enhances appearance. The color-selectable indication and sound-selectable indication increase the options for machine alarms.

The 60 mm tower lights offer high-quality, true-color, bright LED modules with six color choices and sound unit option that enable users to create a configuration best suited to their application needs.

The Harmony XVU tower lights enable quick and flexible installation, either directly on the machine, with a 100 mm pole, or with an adjustable pole. It can also be mounted upright, at an angle, or on the wall using a three-in-one flexible mounting base.





Key Features:

- Innovative and sleek design
- Stackable up to 5 lens units or 4 lens units and a buzzer, per tower
- Six super bright illuminated signaling units (no bulb to replace) available in red, orange, green, blue, yellow (multi-color unit only), and white
- Seven light pattern options steady, blinking (two speeds), flashing (two speeds), or rotating (two speeds) with the multi-color unit
- Available sound unit (buzzer) with up to 85 dB volume
- · Quick and flexible installation
- Two body colors black or silver with 24 VDC or 100 240 VAC voltage options (PNP or NPN)
- IP 65 for illuminated units, with no additional sealing kit needed and IP 54 for buzzer
- CE, UL[®], and CSA[®] certified



Harmony XVU Tower Lights



>XVUC23



>XVUC9S



> XVI JZ05

Description	Voltage	Body Color	Signaling Color	Visual Appearance	Catalog Number
LED Units					
XVU Green LED unit	24 VAC/DC	-	Green	Steady	XVUC23
XVU Red LED unit	24 VAC/DC	-	Red	Steady	XVUC24
XVU Orange LED unit	24 VAC/DC	-	Orange	Steady	XVUC25
XVU Blue LED unit	24 VAC/DC	-	Blue	Steady	XVUC26
XVU White LED unit	24 VAC/DC	-	White	Steady	XVUC27
XVU Multi-color unit	24 VAC/DC	-	Green, Red, Orange, Blue, White, Yellow	Steady, Flashing, Blinking, Rotating	XVUC29
Buzzer Units					
XVU Buzzer unit, Black	24 VAC/DC	Black	-	-	XVUC9S
XVU Buzzer unit, Silver	24 VAC/DC	Sliver	-	-	XVUC9SQ
Body Units					
XVU Body (DC), Black	24 VAC/DC	Black	-	-	XVUC21B
XVU Body (DC), Silver	24 VAC/DC	Sliver	-	-	XVUC21BQ
XVU Body (AC) NPN, Black	100 – 240 VAC	Black	-	-	XVUC21M
XVU Body (AC) PNP, Black	100 – 240 VAC	Black	-	-	XVUC21MP
XVU Body (AC) PNP, Silver	100 – 240 VAC	Silver	-	-	XVUC21MQP
Mounting Units					
XVU Adjustment pole, Black	-	Black	-	-	XVUZ05
XVU Fixing plate with 100 mm pole, Black	-	Black	-	-	XVUZ02
XVU Fixing plate with 100 mm pole, Silver	-	Silver	-	-	XVUZ02Q
XVU Direct mounting plate, Black	-	Black	-	-	XVUZ01
XVU Direct mounting plate, Silver	-	Silver	-	-	XVUZ01Q

1	

>XVUZ06

Description	Voltage	Body Color	Signaling Color	Visual Appearance	Catalog Number
Accessories					
XVU Flexible mounting, Black	-	Black	-	-	XVUZ06
XVU Body extender, Black	-	Black	-	-	XVUC020
XVU Body extender, Silver	-	Silver	-	-	XVUC020Q



Access the Tower Lights Visual Product Configurator
Scan this QR code with your smartphone to access the configurator.



Equip Your Machine with Harmony XVU Scan this QR code to watch a short video.

For more information visit www.schneider-electric.com/us and enter key code d817u.



Schneider Electric USA

8001 Knightdale Boulevard Knightdale, NC 27545 USA Tel: 888-778-2733 www.schneider-electric.com/us