SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company Address: 8125 Cobb Center Drive Kennesaw, GA 30152

Kennesaw, GA 30152	Product Information:	800-TECH-401	Emergency:	(Chemtrec) 800-424-9300
	Customer Service:	800-645-5244	Revision Date:	April 1, 2011
Product Identification				

POW-R-WASH ® VZ						
Product Code: ES6300						
SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS						
Chemical Name	CAS#	Wt. % Range				
1,1,1,2,2,3,4,5,5,5-decafluoropentane	138495-42-8	1.0-30.0				
1,1,1,3,3-pentafluorobutane	406-58-6	0.0-50.0				
trans-1,2-dichloroethylene	156-60-5	10.0-25.0				
1,1,1,2-tetrafluoroethane	811-97-2	35.0-65.0				
methanol	67-56-1	0.1-1.0				

SECTION 3: HAZARD IDENTIFICATION

Emergency Overview: Clear, colorless liquid with faint ethereal odor. This product is nonflammable. Liquid may irritate eyes and skin under repeated or prolonged exposure. Breathing high concentrations of product vapor may produce dizziness and nausea.

Potential Health Effects:

Eyes: Liquid, aerosols and vapors of this product may be irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation. Skin: Prolonged contact can cause skin irritation.

Ingestion: May be harmful if swallowed. Swallowing this material may result in nausea, vomiting and weakness followed by central nervous system depression. Inhalation: Can be harmful if inhaled. High concentrations of vapors in immediate area can cause dizziness, nausea and vomiting.

SECTION 4: FIRST AID MEASURES

Eyes: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

Skin: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persist. Wash clothing before reuse.

Ingestion: If swallowed, do not induce vomiting. If conscious, give 2 glasses of water. Never give anything by mouth to an unconscious person. Keep head below knees to minimize chance of aspirating material into the lungs. Get medical attention immediately.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: None to boiling (TCC)

Extinguishing Media: Use water spray or fog, CO2, dry chemical or water stream when fighting fires involving this material.

Fire Fighting Instructions: As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

<u>Spills:</u> Shut off leak if possible and safe to do so. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7: HANDLING AND STORAGE

Avoid prolonged or repeated contact with eyes, skin, and clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor or mist. Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight. **KEEP OUT OF REACH OF CHILDREN.**

SECTION 8: EXPOSURE CONTROLS/PERSO	NAL PROTECTION		
Exposure Guidelines:			
CHEMICAL NAME	ACGIH TLV	OSHA PEL	OTHER
1,1,1,2,2,3,4,5,5,5-decafluoropentane	NE	NE	200 ppm*
trans-1,2-dichloroethylene	200 ppm	200 ppm	
1,1,1,3,3-pentafluorobutane	NE	NE	
1,1,1,2-tetrafluoroethane	NE	NE	1000 ppm*
methanol	200 ppm	200 ppm	
NE = None Established			

* = Supplier's Occupational Exposure Limit

Work/Hygienic Practices:	Good general ventilation should be sufficient to control airborne levels.	If vapor concentration exceeds TLV, use NIOSH approved organic
vapor cartridge respirator.	Wear safety glasses with side shields or goggles and rubber or other che	emically resistant gloves when handling this material.
NFPA and HMIS Codes:	NFPA	HMIS
Health	1	1
Flammability	0	0
Reactivity	1	1
Personal Protection	-	В

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES Physical State: Clear, colorless liquid Solubility in Water: Negligible Odor: Ethereal Odor Specific Gravity: 1.25 <u>pH:</u> NA (Water =1) Vapor Pressure: 220 mmHg@ 70 F (Liquid) Evaporation Rate: >1 Boiling Point: 95°F (35C) (initial) (Butyl acetate=1) Percent Volatile: 100% Viscosity: NA SECTION 10: STABILITY AND REACTIVITY Stability - This product is stable. Conditions to Avoid: Steam, oxidizers, elevated temperatures. Keep away from elevated temperatures. Do not spray near open flames, red hot surfaces or other sources of ignition. Incompatibility: Do not mix with chemically active metals such as potassium, magnesium, zinc and powdered aluminum, strong base, caustic soda, caustic potash or oxidizing. Products of Decomposition: Thermal decomposition may release carbon monoxide, carbon dioxide, hydrogen chloride and hydrogen fluoride. Hazardous Polymerization: Will not occur Conditions to Avoid: Finely divided active metals, alkali and alkaline earth metals SECTION 11: TOXICOLOGICAL INFORMATION

SECTION II: TOXICOLOGIC	AL INFORMATION				
Inhalation:			Ingestion:		
Tetrafluoroethane	Rat ALC 567,00	0 ppm/4hrs	trans-1,2-dichloroethylene	LD50 rats	>5,000 mg/kg
trans-1,2-dichloroethylene	LC50 rat 24,100	ppm/4hrs	decafluoropentane	DL50 rats	>5,000 mg/kg
decafluoropentane	Rat LC50 11,10	0 ppm/4hrs	pentafluorobutane	LD50 rats	>2,000 mg/kg
pentafluorobutane	LC50 rat >10%	/ 4hrs	methanol	LD50 rats	5,628 mg/kg
methanol	LC50 rats 64,000	ppm/4hrs			
<u>Skin</u>			Eye:		
methanol	20mg/24H MI	LD	methanol	40 mg	MOD
trans-1,2-dichloroethylene	LD50 rabbit >5,0	000 mg/kg	trans-1,2-dichloroethylene	MLI	D-MOD
decafluoropentane	Rabbits ALD >5,0	00 mg/kg			
Cancer Information: No ingredien	ts listed as human carcinoger	ns by NTP or IARC			
Reproductive effects: none	Teratogenic effects	s: none	Mutagenic effects: none		
SECTION 12 ECOLOGICAL	NEODWATION				

SECTION 12: ECOLOGICAL INFORMATION

Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

REPORTING

US regulations require reporting spills of this material that could reach any surface waters.

The toll free number for the US Coast Guard National Response Center is: 1-800-424-8802

SECTION 13: DISPOSAL CONSIDERATIONS Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.							
SECTION 14: TRANSPORTATION IN	FORMATION						
Proper			Sub.	Pkg.	Hazard	Pkg.	Max.
Shipping Name	UN Number	Class	Risk	Group	Label	Instr.	Quantity
<u>Air::</u> Aerosols non-flammable n.o.s.	UN 1950	2.2	NA	NA.	Non-flammable	203 Y203	75 k.g; 150k.g. 30 kg
Ground: Consumer Commodity ORM-D	NA	ORM-D	NA	NA	Gas ORM-D	Pkg. Auth.	30 kg 173.306

SECTION 15: REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

Methanol CAS # 67-56-1 This information should be included on all MSDSs copied and distributed for this material.

TOXIC SUBSTANCES CONTROL ACT (TSCA).

All ingredients of this product are listed on the TSCA Inventory.

WHMIS: Class A; Class D2B

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16: OTHER INFORMATION

This product is a Level 1 aerosol. Do not puncture or incinerate containers. Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.

R

0.1-1.0%