


## High Brightness LED Power Module



22140



22139

### FEATURES

- Metal core PCB: Al > 0.75 thickness
- Single side/single layer PCB
- Shiny white surface
- 12, 24, or 36 LEDs, max. current per LED 1 A
- Conductive top layer: Cu (min. 18  $\mu$ m)
- Isolation layer prepreg > 63  $\mu$ m
- Standard solder mask material
- ESD withstand voltage: up to 2 kV according to JESD22-A114-B
- LM80 certified LEDs
- Compliant to RoHS Directive 2002/95/EC



### Note

\*\* Please see document "Vishay Material Category Policy":  
[www.vishay.com/doc?99902](http://www.vishay.com/doc?99902)

### DESCRIPTION

The VLSL40xxA are metal core based high brightness LED power modules, assembled with 12, 24 or 36 HB white LEDs. The color temperature is cool white in the typical range of 5000 K to 7000 K. The modules are designed for flexible use due to the option for using special reflectors to adjust the emission characteristics.

### APPLICATIONS

- Streetlight
- Internal lighting in buildings
- Tunnel lights
- General lighting application

### PRODUCT GROUP AND PACKAGE DATA

- Product group: LED
- Package: LED module
- Product series: power
- Angle of half intensity:  $\pm 80^\circ$

PARTS TABLE				
PART	COLOR	LUMINOUS FLUX (at $I_F = 700$ mA typ.)	COLOR TEMPERATURE K	TECHNOLOGY
VLSL4012A	Cool white	$\Phi_V = 2100$ lm	5000 to 7000	InGaN
VLSL4024A	Cool white	$\Phi_V = 4200$ lm	5000 to 7000	InGaN
VLSL4036A	Cool white	$\Phi_V = 6300$ lm	5000 to 7000	InGaN

ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25$ °C, unless otherwise specified) VLSL4012A, VLSL4024A, VLSL4036A				
PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Forward current	Per row	$I_F$	750	mA
Power dissipation VLSL4012A	Total (max.)	$P_{tot}$	35	W
Power dissipation VLSL4024A		$P_{tot}$	69	W
Power dissipation VLSL4036A		$P_{tot}$	104	W
Junction temperature		$T_j$	120	°C
Operating temperature range		$T_{amb}$	- 40 to + 85	°C
Storage temperature range		$T_{stg}$	- 40 to + 85	°C



**OPTICAL AND ELECTRICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)  
**VLSL4012A, COOL WHITE**

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous flux per row <sup>(1)</sup>	$I_F = 700\text{ mA}$	$\Phi_V$	860	1050	-	lm
Luminous flux total <sup>(1)</sup>	$I_{board} = 2 \times 700\text{ mA}$	$\Phi_V$	1720	2100	-	lm
Color temperature	$I_F = 700\text{ mA}$	TK	5000	-	7000	K
Forward voltage per row	$I_F = 700\text{ mA}$	$V_F$	19	21	23	V
Class A ( $V_{Fmax.} - V_{Fmin.}$ ) all rows <sup>(2)</sup>	$I_F = 700\text{ mA}$	$\Delta V_F$	-	-	0.9	V
Temperature coefficient of $V_F$ per row	$I_F = 350\text{ mA}$	$TC_{V_F}$	-	-20	-	mV/K
Temperature coefficient of $\Phi_V$	$I_F = 350\text{ mA (per row)}$	$TC\Phi_V$	-	-0.4	-	%/K

**Notes**

- Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of  $\pm 0.1\text{ V}$ . Luminous flux is measured at a current pulse duration of 25 ms and an accuracy of  $\pm 11\%$ .
- <sup>(1)</sup> Calculated based on single LED unit.
- <sup>(2)</sup>  $V_F$  classes are marked at the LED cluster and represent the technical classification only. The single groups cannot be specifically ordered.

**OPTICAL AND ELECTRICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)  
**VLSL4024A, COOL WHITE**

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous flux per row <sup>(1)</sup>	$I_F = 700\text{ mA}$	$\Phi_V$	860	1050	-	lm
Luminous flux total <sup>(1)</sup>	$I_{board} = 4 \times 700\text{ mA}$	$\Phi_V$	3440	4200	-	lm
Color temperature	$I_F = 700\text{ mA}$	TK	5000	-	7000	K
Forward voltage per row	$I_F = 700\text{ mA}$	$V_F$	19	21	23	V
Class A ( $V_{Fmax.} - V_{Fmin.}$ ) all rows <sup>(2)</sup>	$I_F = 700\text{ mA}$	$\Delta V_F$	-	-	0.9	V
Temperature coefficient of $V_F$ per row	$I_F = 350\text{ mA}$	$TC_{V_F}$	-	-20	-	mV/K
Temperature coefficient of $\Phi_V$	$I_F = 350\text{ mA (per row)}$	$TC\Phi_V$	-	-0.4	-	%/K

**Notes**

- Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of  $\pm 0.1\text{ V}$ . Luminous flux is measured at a current pulse duration of 25 ms and an accuracy of  $\pm 11\%$ .
- <sup>(1)</sup> Calculated based on single LED unit.
- <sup>(2)</sup>  $V_F$  classes are marked at the LED cluster and represent the technical classification only. The single groups cannot be specifically ordered.

**OPTICAL AND ELECTRICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)  
**VLSL4036A, COOL WHITE**

PARAMETER	TEST CONDITION	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous flux per row <sup>(1)</sup>	$I_F = 700\text{ mA}$	$\Phi_V$	860	1050	-	lm
Luminous flux total <sup>(1)</sup>	$I_{board} = 6 \times 700\text{ mA}$	$\Phi_V$	5160	6300	-	lm
Color temperature	$I_F = 700\text{ mA}$	TK	5000	-	7000	K
Forward voltage per row	$I_F = 700\text{ mA}$	$V_F$	19	21	23	V
Class A ( $V_{Fmax.} - V_{Fmin.}$ ) all rows <sup>(2)</sup>	$I_F = 700\text{ mA}$	$\Delta V_F$	-	-	0.9	V
Temperature coefficient of $V_F$ per row	$I_F = 350\text{ mA}$	$TC_{V_F}$	-	-20	-	mV/K
Temperature coefficient of $\Phi_V$	$I_F = 350\text{ mA (per row)}$	$TC\Phi_V$	-	-0.4	-	%/K

**Notes**

- Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of  $\pm 0.1\text{ V}$ . Luminous flux is measured at a current pulse duration of 25 ms and an accuracy of  $\pm 11\%$ .
- <sup>(1)</sup> Calculated based on single LED unit.
- <sup>(2)</sup>  $V_F$  classes are marked at the LED cluster and represent the technical classification only. The single groups cannot be specifically ordered.



## COLOR RANGE AND COLOR BINNING

VLSL4012A, VLSL4024A, VLSL4036A: 5000 K to 7000 K group 6P to 7R






Fig. 1 - Chromaticity Coordinates of Colorgroups




## PCB BASIC DESIGN VLSL4012A DIMENSIONS in millimeters



Not indicated tolerances ± 0.15




Drawing-No.: 9.920-6726.03-4  
 Issue:1; 11.05.10  
 22137




Assembled with all jumpers. Jumpers can be removed according driver design




## PCB BASIC DESIGN VLSSL4024A DIMENSIONS in millimeters



Not indicated tolerances ± 0.15




Drawing-No.: 9.920-6726.02-4  
 Issue:1; 11.05.10  
 22136




Assembled with all jumpers. Jumpers can be removed according driver design


## PCB BASIC DESIGN VL4036A DIMENSIONS in millimeters



Not indicated tolerances ± 0.15



Drawing-No.: 9.920-6726.01-4  
 Issue:1; 11.05.10  
 22135



Assembled with all jumpers. Jumpers can be removed according driver design

## PCB CHARACTERISTICS

- Metal core PCB with typical Al thickness of 800  $\mu\text{m}$
- Prepreg thickness typical 127  $\mu\text{m}$
- Conductive pattern Cu typical 25  $\mu\text{m}$
- Total board thickness: 1 mm  $\pm$  15 %
- Warp max. 0.75 % of board dimension
- Solder resist on top side
- Shiny white surface
- Galvanic of solder pads pure matte Sn ( $\geq$  0.8  $\mu\text{m}$ ), immersion plated
- Assembled with 12, 24 or 36 high brightness power LEDs. LED position accuracy  $\pm$  0.125 mm from middle axis, horizontal tilt max. 2°

## EMISSION CHARACTERISTICS




Fig. 2 - Rel. Luminous Intensity vs. Angular Displacement





Fig. 3 - Sample Board with Reflectors (for Info only)

## BAR CODE PRODUCT LABEL



- A. Type of component
- B. Manufacturing plant
- C. SEL - selection code (bin):  
e.g.: code for  $V_F$  class (A, B, C)
- D. Batch:  
200707 = year 2007, week 07  
PH19 = plant code
- E. Total quantity



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**