



Compact Digital Sound Level Meter Model 72-935

Ultra compact sound level meter measures less than 6" in length, including the windscreen, and provides full 40 ~ 130dB measuring range. Perfect for numerous types of measurement including sound system testing and noise level monitoring.

Features:

- Simple one-button operation
- Selectable MIN/MAX hold
- Large 3/4" digit LCD backlit display
- Threaded insert which accepts standard tripod mount
- Auto power off
- 1999 count display with 0.1dB resolution
- Removable windscreen
- Includes manual and 9V battery

Specifications:

Frequency range:	31.5Hz ~ 8KHz
Measuring level range:	40.0 ~ 130.0dB
Frequency weighting:	A
Microphone:	1/2 inch electret condenser
Display:	LCD
Digital display :	4 digits, 1999 count Resolution: 0.1dB Refresh rate: 0.5 sec.
Time weighting:	125mS
Accuracy:	± 3.5dB @1kHz, 94dB (under reference conditions)
Alarm function:	Displays "OVER" when input exceeds 130dB
Auto power off:	After approximately 15 minutes of inactivity
Power supply:	One 9V battery, 006P or IEC 6F22 or NEDA 1604
Operation temperature:	0 ~ 40°C (32 ~ 104°F)
Operation humidity:	10 ~ 90% RH
Storage temperature:	-10 ~ 60°C (14 ~ 140°F)
Storage humidity:	10 ~ 75% RH
Dimension:	5 1/4" (L) x 2" (W) x 1 1/4" (D)
Weight:	135g (including battery)
Included accessories:	9V battery, instruction manual

