



Millimeter Graduation Styles

30

First Edge: None Second Edge: 1/2mm

Fourth Edge: 1/2mm

Third Edge: mm

14mm10 20 30 40 50 60 70 80 90 100 110 120 130 140

35

Reads both left-to-right and right-to-left. A Starrett original feature. First Edge: mm

Second Edge: 1/2mm

Fourth Edge: mm

Third Edge: 1/2mm

35E

First Edge: mm

End Graduations: mm

Second Edge: 1/2mm

Fourth Edge: mm

Third Edge: 1/2mm

37

First Edge: mm

Second Edge: 1/2mm

Fourth Edge: 1/2mm

Third Edge: mm

37E

First Edge: mm

End Graduations: mm

Second Edge: 1/2mm

Fourth Edge: 1/2mm

Third Edge: mm

01-1	130	130	110	OOI NLC635	06	0S STAR	0.L	09	00 TEMPERED	01	30	30	10
imm10	20	30	40	50	60	70	80	90	100	110	120	130	140
وللتأوليا	Marile	alle alle	والماولان	أعللهاءللوا	والمأوال	بالبدلاء	والعادلك	Milde	اعتباعتنا	وللمليك	علاءاءلنا	عللماللنا	وأبلامايلاما
dallalili	AL LAL	dial.	.11.1.11.	31,4,11,	H. III.	alfalalfa	dial di	111,1,11,	1,11,1,11,1	dida.	dhalab.	diddi.	dbldtd.
or	08	30	01	20	09	04	08	06	001	OII	120	130	0#I

₫ OFI	130	120	OLL	00I NLC635E	06	08	04	09	20	OF	30	30	
10 Lulud	20	30	40	50	60	70	80	90	100	110	120	130	140
uninini		PIPPIP	rarana.	191191919	Helite	981919	919919	9119319	DATE DE LE PERSONNE	alatala managa		HILITI	
um OI	50	30	07	20	09	04	08	06	100	110	130	130	0+I
		120	110	100	90	80	70	60	50	40	30	20	10,

NAC637 STARRETT TEMPERED	140
	140

andandan.	andana	halana	Tillian	Aldali.	Male	distant.	alla alla	latelati	landan.	distant	attalatta	distilla	वानवानवान
10 10	20	30	40	50	60	70	80	90	100	110	120	130	140
10	20	30	40	50	60	70	80	90	100	110	120	130	140
aldaldala	hillibili	lata lata	dhidh	dhddi	lata lata	littilitti	landa.	بالتأباليا	hillidi	dhidle	diddi	hilidi	landandan



NOTE: All rules under 25mm in width have single row of millimeter figures. Rules 25mm and wider have double row of millimeter figures, and each edge represents the bottom edge reading left to right.





Steel Rules with Millimeter Graduations

150-1800mm

All rules furnished with Starrett satin chrome finish, except where noted. Additional sizes and variations available on special order.

Rules include:

- Full-Flexible
- Semi-Flexible
- Spring-Tempered
- · Heavy Spring-Tempered

Catalog Number Legend:

Prefixes:

C - Satin Chrome Finish

Suffixes:

E - End Graduations

N - Narrow-Type Rule

S - Semi-Flexible

ength	Width x Thickness	Graduations	Feature Remarks	Catalog No.	EDP
				*C330-150	51329
150mm	12.7 x 0.4mm	30 – 1/2mm One Side; mm and 1/2mm on Reverse	With Standard Letter of Certification**	*C330-150 W/SLC	66882
50mm S	pring-Tempered Steel	Rules with Millimeter Graduations			
		35 – mm and 1/2mm Both Sides		C635-150	52630
	19 x 1.2mm	35 – IIIII and 1/2mm bout Sides	With Standard Letter of Certification**	C635-150 W/SLC	66893
150mm 4.8 x 1.2mm		35E - mm and 1/2mm Both Sides; mm on Both Ends One Side	End Graduations	C635E-150	55968
	35 - mm One Edge and 1/2mm One Edge on Reverse	Narrow Rule, Regular Steel Finish	635N-150	70164	
	10 v 1 0mm	37 - mm and 1/2mm Both Sides		C637-150	56049
	19 x 1.2mm	37E – mm and 1/2mm Both Sides; mm on Both Ends One Side	End Graduations	C637E-150	55969
00mm F	ull-Flexible Steel Rules	s with Millimeter Graduations			
300mm 12.7 x 0.4mm		30 – 1/2mm One Side; mm and 1/2mm on Reverse		*C330-300	51330
DUUIIIII	12.7 X U.4111111	30 – 1/2mm one Side, mm and 1/2mm on neverse	With Standard Letter of Certification**	*C330-300 W/SLC	66883
300mm S	emi-Flexible Steel Rul	es with Millimeter Graduations			
300mm	25.4 x 0.5mm	35 – mm and 1/2mm Both Sides		C335S-300	56048
00mm S	pring-Tempered Steel	Rules with Millimeter Graduations			
300mm	25.4 x 1.2mm	35 – mm and 1/2mm Both Sides		C635-300	52631
300111111	23.4 X 1.2111111	33 - IIIIII aliu 1/2111111 bout Sides	With Standard Letter of Certification**	C635-300 W/SLC	66894
500mm S	pring-Tempered Steel	Rules with Millimeter Graduations			
500mm	29 x 1.2mm	35 – mm and 1/2mm Both Sides		C635-500	52632
000mm	Spring-Tempered Stee	I Rules with Millimeter Graduations			
000mm	32 x 1.2mm	35 – mm and 1/2mm Both Sides		C635-1000	52633
800mm l	Heavy Spring-Tempere	d Steel Rules with Millimeter Graduations			
1800mm	38 x 2.5mm	35 - mm and 1/2mm Both Sides		C635-1800MM	64299

^{**} Includes redemption card for Standard Letter of Certification (SLC).

^{*} Indicates rules with single row of millimeter figures (all rules under 25mm width). Rules without asterisk have double row of millimeter figures, and each edge represents the bottom edge reading left to right (rules 25mm and wider).