Model 3789
BNC Male To Minigrabber®
Test Clip Breakout



FEATURES:

- Minigrabber® test clip hooks attach to terminal sizes up to .060" diameter
- Converts BNC (Female) jacks to Minigrabber test clips for test versatility
- BNC connector and Minigrabber test clip caps are molded directly onto the wire for pull strength durability and dust and moisture resistance
- Grabber hook and BNC center contact are Gold-plated Beryllium Copper for optimum strength, excellent corrosion resistance and low contact resistance to ensure test signal integrity
- Schematic: Black Minigrabber test clip to BNC shell, red Minigrabber test clip to BNC center contact

MATERIALS:

BNC: Nickel plated brass
Center Contact: Gold-plated brass
Insulation: polypropylene molded to BNC and wire
Wire: 20 AWG, PVC
Marking: "POMONA 3789"
Minigrabber® test clip:
Contact: Gold-plated Beryllium Copper,
Insulation: Glass filled nylon, color: red and black
Marking: "Pomona Electronics", "Minigrabber®"

RATINGS:

Operating Temperature: +55°C (+131°F) Max.
Operating Voltage: Hand-held testing: 30VAC/60VDC Max.
Hands free testing in controlled voltage environments: 300VRMS Max.

ORDERING INFORMATION: Model 3789

All dimensions are in inches.
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA

Sales: 800-490-2361 Fax: 888-403-3360
Technical Assistance: 800-241-2060

Pomona*ACCESS* **90334** (800) 444-6785 or (425) 446-6010
More drawings available at www.pomonaelectronics.com