

# Safety Data Sheet according to Regulation (EC) No1907/2006

Page 1 of 12

SDS No.: 168431 V005.10

Revision: 02.05.2014

printing date: 22.11.2014

LOCTITE 577

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE 577

#### **Contains:**

Maleic acid

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Anaerobic Adhesive

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (CLP):

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

### Classification (DPD):

Sensitizing

R43 May cause sensitisation by skin contact.

### 2.2. Label elements

### Label elements (CLP):





MSDS-No.: 168431 LOCTITE 577 Page 2 of 12

V005.10

#### Label elements (DPD):

#### Xi - Irritant



### Risk phrases:

R43 May cause sensitisation by skin contact.

### Safety phrases:

S24 Avoid contact with skin.

S37 Wear suitable gloves.

S51 Use only in well-ventilated areas.

### Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

### Contains:

Maleic acid

### 2.3. Other hazards

None if used properly.

### **SECTION 3: Composition/information on ingredients**

### General chemical description:

Anaerobic Sealant

MSDS-No.: 168431 LOCTITE 577 Page 3 of 12

V005.10

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.  Lauryl methacrylate	REACH-Reg No. 205-570-6	1-< 6 %	Serious eye irritation 2
142-90-5	203-370-0	1- < 0 %	H319
			Skin irritation 2
			H315 Specific target organ toxicity - single
			exposure 3
			H335
Hexadecyl methacrylate	219-672-3	1-< 2 %	Specific target organ toxicity - single
2495-27-4			exposure 3 H335
			Skin irritation 2
			H315 Serious eye irritation 2
			H319
	210.025.0	1 20/	
Tetradecyl methacrylate 2549-53-3	219-835-9	1-< 2 %	Specific target organ toxicity - single exposure 3
			H335
			Skin irritation 2 H315
			Serious eye irritation 2
			Н319
Acetic acid, 2-phenylhydrazide	204-055-3	0,1-< 1 %	Acute toxicity 3; Oral
114-83-0			H301 Acute toxicity 4; Dermal
			H312
			Skin irritation 2; Dermal H315
			Serious eye irritation 2
			H319
			Acute toxicity 4; Inhalation H332
			Specific target organ toxicity - single
			exposure 3; Inhalation H335
			Carcinogenicity 2
			H351
Maleic acid	203-742-5	>= 0,1-< 1 %	Acute toxicity 4; Oral
110-16-7	01-2119488705-25		H302 Acute toxicity 4; Dermal
			H312
			Skin irritation 2 H315
			Skin sensitizer 1
			H317 Serious eye irritation 2
			H319
			Specific target organ toxicity - single exposure 3
			H335
Company local control of	201 254 7	0.1 - 1.0/	A out of the day D
Cumene hydroperoxide 80-15-9	201-254-7	0,1-< 1 %	Acute toxicity 4; Dermal H312
			Specific target organ toxicity - repeated
			exposure 2 H373
			Acute toxicity 4; Oral
			H302 Organic peroxides E
			H242
			Acute toxicity 3; Inhalation H331
			Skin corrosion 1B
			H314 Chronic hazards to the aquatic environment 2
			H411
1,4-Naphthalenedione	204-977-6	0,01-< 0,1 %	Aguta tovinity 2: Omal
1,4-Naphthalehedione 130-15-4	204-911-U	0,01- < 0,1 %	Acute toxicity 3; Oral H301

MSDS-No.: 168431 LOCTITE 577 Page 4 of 12

V005.10

Skin irritation 2; Dermal
H315
Skin sensitizer 1; Dermal
H317
Serious eye irritation 2
H319
Acute toxicity 1; Inhalation
H330
Specific target organ toxicity - single
exposure 3; Inhalation
H335
Acute hazards to the aquatic environment 1
H400
Chronic hazards to the aquatic environment 1
H410
M factor: 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Lauryl methacrylate 142-90-5	205-570-6	1 - < 6 %	Xi - Irritant; R36/37/38
Hexadecyl methacrylate 2495-27-4	219-672-3	1 - < 2 %	Xi - Irritant; R36/37/38
Tetradecyl methacrylate 2549-53-3	219-835-9	1 -< 2 %	Xi - Irritant; R36/37/38
Maleic acid 110-16-7	203-742-5 01-2119488705-25	>= 0,1 -< 1 %	Xn - Harmful; R21/22 Xi - Irritant; R36/37/38, R43
Cumene hydroperoxide 80-15-9	201-254-7	0,1 - < 1 %	T - Toxic; R23 Xn - Harmful; R21/22, R48/20/22 C - Corrosive; R34 O - Oxidizing; R7 N - Dangerous for the environment; R51/53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting. Seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

 $\textbf{4.3.} \ \textbf{Indication of any immediate medical attention and special treatment needed}$ 

See section: Description of first aid measures

MSDS-No.: 168431 LOCTITE 577 Page 5 of 12

V005.10

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Carbon dioxide, foam, powder

#### Extinguishing media which must not be used for safety reasons:

None known

#### 5.2. Special hazards arising from the substance or mixture

None

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### **Additional information:**

In case of fire, keep containers cool with water spray.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact.

Ensure adequate ventilation.

See advice in section 8

#### **6.2. Environmental precautions**

Do not let product enter drains.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

Dispose of contaminated material as waste according to Section 13.

### **6.4.** Reference to other sections

See advice in section 8

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

#### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

### 7.3. Specific end use(s)

Anaerobic Adhesive

MSDS-No.: 168431 LOCTITE 577 Page 6 of 12

V005.10

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient	ppm	mg/m <sup>3</sup>	Type	Category	Remarks
SILICA, AMORPHOUS, INHALABLE		6	Time Weighted Average		EH40 WEL
DUST			(TWA):		
112945-52-5					
SILICA, AMORPHOUS, RESPIRABLE		2,4	Time Weighted Average		EH40 WEL
DUST			(TWA):		
112945-52-5					

### **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value			Remarks	
			mg/l	ppm	mg/kg	others	
Maleic acid 110-16-7	aqua (freshwater)					0,074 mg/L	
Maleic acid 110-16-7	aqua (intermittent releases)					0,744 mg/L	
Maleic acid 110-16-7	sediment (freshwater)				0,0624 mg/kg		
Maleic acid 110-16-7	STP					3,33 mg/L	

### **Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Maleic acid 110-16-7	worker	Dermal	Acute/short term exposure - local effects		0,55 mg/cm2	
Maleic acid 110-16-7	worker	Dermal	Long term exposure - local effects		0,04 mg/cm2	
Maleic acid 110-16-7	worker	Dermal	Acute/short term exposure - systemic effects		58 mg/kg bw/day	
Maleic acid 110-16-7	worker	Dermal	Long term exposure - systemic effects		3,3 mg/kg bw/day	

### **Biological Exposure Indices:**

None

### 8.2. Exposure controls:

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A

MSDS-No.: 168431 **LOCTITE 577** Page 7 of 12

V005.10

#### Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

### **SECTION 9: Physical and chemical properties**

< 300 mbar

### 9.1. Information on basic physical and chemical properties

Appearance yellow Odor

Odour threshold No data available / Not applicable

3 - 6 pН

0

Initial boiling point Not determined

Flash point No data available / Not applicable Decomposition temperature No data available / Not applicable

Vapour pressure < 5 mm hg

(27 °C (80.6 °F))

Vapour pressure

(50 °C (122 °F))

Density 1,15 - 1,20 g/cm3

Bulk density No data available / Not applicable No data available / Not applicable Viscosity Viscosity (kinematic) No data available / Not applicable Explosive properties No data available / Not applicable

Solubility (qualitative) Slight

(23 °C (73.4 °F); Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Explosive limits Partition coefficient: n-octanol/water No data available / Not applicable

Not available. Evaporation rate Not available. Vapor density

Oxidising properties No data available / Not applicable

### 9.2. Other information

No data available / Not applicable

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reaction with strong acids.

Reacts with strong oxidants.

MSDS-No.: 168431 LOCTITE 577 Page 8 of 12

V005.10

#### 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

#### 10.4. Conditions to avoid

Stable

#### 10.5. Incompatible materials

See section reactivity

#### 10.6. Hazardous decomposition products

Irritating organic vapours. carbon oxides.

### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Oral toxicity:

This material is considered to have low toxicity if swallowed.

#### Inhalative toxicity:

May cause irritation to respiratory system.

#### Skin irritation:

Prolonged or repeated contact may cause skin irritation.

#### Eye irritation:

May cause mild irritation to the eyes.

#### Sensitizing:

May cause an allergic skin reaction.

#### Acute oral toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LD50	550 mg/kg	oral		rat	

### Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		

#### Acute dermal toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		

#### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	

MSDS-No.: 168431 LOCTITE 577 Page 9 of 12

V005.10

#### Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	

### **SECTION 12: Ecological information**

### General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation 1272/2008/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Other adverse effects:

Do not empty into drains, soil or bodies of water.

### 12.1. Toxicity

#### **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity	Exposure time	Species	Method
			Study			
Maleic acid 110-16-7	LC50	> 245 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Maleic acid 110-16-7	EC50	245 mg/l	Daphnia	24 h	Daphnia magna	
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	EC50	0,011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline 201 (Alga, Growth Inhibition Test)

### 12.2. Persistence and degradability

### Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

MSDS-No.: 168431 LOCTITE 577 Page 10 of 12

V005.10

Maleic acid 110-16-7	readily biodegradable	aerobic	87 - 88 %	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed Bottle Test)
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4		no data	0 - 60 %	OECD 301 A - F

### 12.3. Bioaccumulative potential / 12.4. Mobility in soil

#### Mobility:

Cured adhesives are immobile.

#### **Bioaccumulative potential:**

No data available.

Hazardous components CAS-No.	LogKow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Acetic acid, 2- phenylhydrazide 114-83-0	0,74					
Maleic acid 110-16-7	-0,48					
Cumene hydroperoxide 80-15-9		9,1		calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
Cumene hydroperoxide 80-15-9	2,16					
1,4-Naphthalenedione 130-15-4	1,71					

#### 12.5. Results of PBT and vPvB assessment

Hazardous components CAS-No.	PBT/vPvB
Maleic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
110-16-7	Bioaccumulative (vPvB) criteria.

#### 12.6. Other adverse effects

No data available.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

MSDS-No.: 168431 LOCTITE 577 Page 11 of 12

V005.10

### **SECTION 14: Transport information**

### 14.1. UN number

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

### 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

#### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

### 14.4. Packaging group

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

#### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

#### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (1999/13/EC) < 3 %

### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 168431 LOCTITE 577 Page 12 of 12

V005.10

### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R21/22 Harmful in contact with skin and if swallowed.

R23 Toxic by inhalation.

R34 Causes burns.

R36/37/38 Irritating to eyes, respiratory system and skin.

R43 May cause sensitisation by skin contact.

R48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R7 May cause fire.

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.