



BRR.2S.200.PZVG

MECHANICAL DETAILS

Shell Style Model BRR* : Cap spring loaded dust cap for ERA ERN and EG receptacle or PSA and PK fixed receptacle

Keying

Housing Material PSU(Polysulfone) shell without treatment, FKM (VITON®)

Cable Fixing 0 - 0 mm

Variant 2 G : Grey

	Col	Col	Col	Col	Col	Col	Col	Col
Mm.								
In.								

PERFORMANCE DETAIL

Insert :

Insulator

Insulator

OTHER CHARACTERISTICS

- Endurance (Shell)** Endurance (Shell):
- Temp (min)** -50°C
- Temp (max)** +150°C
- Humidity (max):** <=95% [at 60 deg C /140 F]
- Vibration:** 15 g [10 Hz - 2000 Hz]
- Shock Resistance:** 100 g [6 ms]
- Salt Spray** >144 hr
- Climatical** 50/175/21
- Shielding (min):** 75 dB (10 MHz)
- Shielding (min):** 40 dB (1 GHz)
- IP Rating** 50



Available Download

[Coax_triax_mixed_en.pdf](#)

Related links

- [Contact](#)
- [Quote Request](#)
- [Catalogs Downloads](#)
- [Catalogs Requests](#)
- [Sample Request](#)
- [3D drawings](#)