



# Process Meter

## with trurange™ technology

Easy to Use. Easy to Read.

**Programmable dynamic backlight color**

**Warning flash**

**0 to +/- 10V / 4-20mA / 10-50mA**  
User selectable Voltage & Current

**0.1% Accuracy**

**40** segment curved bar graph display

**Combined digital and bar graph display**

**Programmable scale**

**WIDE viewing angle**

**USB 2.0**  
USB port for custom user settings

**Full 4 digit readout for accuracy**

**trurange™ technology**

**user configurable linearization**

**INPUT**

**2** alarm set points

**Less than 53mm deep**

**2 outputs - digital and analog**

**Programmable 4 digit star-burst display**

**Custom messages & annunciators**

Featuring an acclaimed easy-to-read display and a versatile set of inputs, the Process Meter takes the APM into a wide range of new industrial applications.

The programmable scale and custom annunciators mean users can tailor the meter to display their critical parameters exactly how they want, while the dynamic backlighting, in conjunction with setpoints, means operators are visually alerted when a parameter is out of range. The two outputs can be used to control other systems in the process, meaning the APM Process Meter is much more than just a display.

trurange™ technology brings a greater level of accuracy to the APM range through innovative input signal optimization. By using this technology, accuracy of 0.1% or better is now achieved, allowing for more precise measurement, display and control. Non-linear sensors, such as thermocouples and pressure transducers, can also be used thanks to the new APM Configurator application that allows the user to configure upto 20 points in a non-linear conversion table.

## Key Features

### Large multi-format display that incorporates:

- 40 segment bar graph display
- Large 4-digit display
- Separate Starburst display area for annunciators, custom messages and alarm information
- Dynamic backlight color


### Programmable:

- Display Range (Both Min & Max Values)
- Custom annunciators
- User-selectable backlight color and intensity
- Two independent alarm set-points
- Two independent outputs
- 4-20mA analog retransmission output

### Visibility:

- User-adjustable backlight brightness and color
- Large display
- Wide viewing angle (horizontal and vertical)
- Custom annunciators

### Dimensions:



Panel cutout: 68mm x 68mm [2.68" x 2.68"] as per DIN43700/IEC61554

INPUT	VOLTAGE	CURRENT
Range (DC)	0 to +/-10VDC	0 - 50mA
Impedance	100K $\Omega$	15 $\Omega$
Accuracy	0.1% of input or 5mV whichever is greater	0.01% of input or 5uA whichever is greater

### ENVIRONMENTAL

Temperature - operating	-10 to +60°C
Temperature - storage	-40 to +70°C
IP rating (from the front)	IP65

### POWER SUPPLY

Nominal Input (AC or DC)	12-24 VAC/VDC
Max Power	1.6W

### DISPLAY

Number of digits	4
Digit height	12mm [0.47"]
Number of message characters	4
Message character height	6mm [0.236"]
Backlight colors	Red, Green, White
LCD display	Positive or Negative

### OUTPUTS


Max voltage	24V
Max current	50mA
Analog output	4-20mA

### CERTIFICATION

UL and cUL (Pending), CE

## Easy To Use Software

Just plug into any USB port on your PC, run the freely available APM Configurator application and you're off. No drivers required.



### Part Numbers:

APM-PROC-APO	APM Process Meter, Positive LCD with outputs
APM-PROC-ANO	APM Process Meter, Negative LCD with outputs
022128-01	USB Cable

Full specifications available online


[www.truAPM.com](http://www.truAPM.com)



## Fluid Level Application

The APM Process Meter is used to display the volume of fluid in the tank. The 4-20mA analog output from the fluid level sensor is scaled to gallons, and the custom annunciator set to "Gal", all via the easy-to-use software application.

High and low setpoints are configured so that the normal green display will flash red when the tank is too full or empty, thereby alerting the operator. Additionally the APM digital outputs are integrated into the tank pumping system and the tank is automatically drained or filled if the setpoints are exceeded.




## Silo Volume Application

The APM Process Meter is used to display the volume of material in the silo, using the analog output from a level sensor.

The signal from the sensor is scaled to measure cubic meters, and the annunciator customised to  $m^3$ , all via the easy-to-use software. Due to the irregular shape of the silo, the 20-point linearization table is used to correct the non-linear signal from the sensor.

The displayed value accurately shows the volume in the silo. High or low setpoints can be set, and the APM can be integrated into other systems for process control.



Full specifications available online [www.truAPM.com](http://www.truAPM.com)

