



Kvaser USBcan Light 2xHS

EAN: 73-30130-00714-7

The Kvaser USBcan Light 2xHS is a compact, reliable and cost-effective means of connecting two high speed CAN busses to a PC or mobile computer. With a USB 2.0 compliant connector at one end and two 9-pin D-SUB connectors at the other, the Kvaser USBcan Light 2xHS is a fraction larger than the one-channel Leaf Light v2 but features the same sleek, ergonomically designed housing that Kvaser products have become renowned for and comes with galvanic isolation as standard.

The Kvaser USBcan Light 2xHS offers two high speed CAN channels and one USB

2.0 compliant interface. With the three connectors at the end of fully galvanically isolated flexible wires, this device is designed to facilitate any application in which the CAN bus connectors aren't easily accessible, such as hard to reach electronic control units (ECU) on a vehicle.

USBcan Light 2xHS is supplied with CANlib, the software API that is common to all Kvaser hardware. Taking just 30 seconds to programme once you have Canlib downloaded on the host computer, USBcan Light 2xHS is simple to install and configure.

Major features of the USBcan Light 2xHS

- One USB 2.0 compliant device provides easy access to two CAN busses.
- Quick and easy plug-and-play installation.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- 100% compatible with applications written for other Kvaser CAN hardware with Kvaser CANlib.
- High-speed CAN connection (compliant with ISO 11898-2), up to 1 Mbit/s.
- Fully compatible with J1939, CANopen, NMEA 2000R and DeviceNet.

TECHNICAL DATA - KVASER USBCAN LIGHT 2XHS

GALVANIC ISOLATION		Yes
BITRATE		40-1000 kbit/s
SILENT MODE		No
ERROR FRAME GENERATION		No
ERROR FRAME DETECTION		Yes
WEIGHT		150g
TIMESTAMP RESOLUTION		2µs
ON BOARD BUFFER		Yes
MAXIMUM MESSAGE RATE, SEND		8000
MAXIMUM MESSAGE RATE, RECEIVE		8000
SOUND		No
CLOCK SYNCHRONIZATION		N/A
DIMENSIONS (WXLXH)		50x90x25mm



TEMPERATURE RANGE	-20°C to +70°C
ORDER NUMBER	73-30130-00714-7

The information herein is subject to change without notice

Kvaser AB
Aminogatan 25
SE-431 53 Mölndal, Sweden
Telephone: +46 (0)31 88 63 44
E-mail: sales@kvaser.com
www.kvaser.com