DESCO INDUSTRIES INC. Technical Bulletin TB-3057

Statguard® Floor Mat Cleaner **Application Instructions**







Figure 1. 1 Quart Spray Bottle (10443)



Figure 2. 2.5 Gallon Bag-in-Box (10444)



Figure 3. 5 Gallon Bag-in-Box (10445)

Description

Desco's Statguard® Floor Mat Cleaner is a non-hazardous, silicone free liquid used to remove dust, grease, grime, shoe prints, and other contaminates from ESD floor mats to maintain the performance of the mats. To apply the cleaner, the floor mat surface should be sprayed until slightly wet and then mopped till dry with a lint free flat mop. No additional rinsing will be required in most cases. Statguard® Floor Mat Cleaner contains no alkali, ammonia, or other harsh chemical that may physically damage mats or degrade the mat's ESD properties. Statguard® Floor Mat Cleaner is formulated to meet the VOC requirements of the California Air Resources Board and it is non-flammable, making it safe to use in electronics production areas and safe for operator contact.

Features

- Vinyl and Rubber Floor Mat Liquid Cleaning Solution
- Simple Application Does Not Require Additional Rinsing
- Silicone Free
- Contains No Chemicals That Will Damage Mats
- Meets CARB VOC Standard, Non-Flammable, Non-Hazardous

Directions for Use

- 1. Use dust mop or broom to remove larger debris from the
- 2. Spray floor mat till slightly wet.
- 3. Mop/scrub till dry with a lint free flat mop.

No additional rinsing is required. For tougher stains reapplication may be necessary.

Specifications

Appearance of solution: Transparent violet

6-8 pH:

Slight floral Odor: Solubility:

Water, acetone,

alcohols

Flammability: Non-flammable

Ion Level: (mg/I)

Fluoride 0.3 Sulfate < 0.5 Nitrate 1.2 Bromide < 0.5 < 0.5 Phosphate

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Web Site: DescoIndustries.com

Electrical Properties (Dry Film): 1 x 107 to <1 x 108

ohms ref. ANSI/ESD S4.1)

Static Decay Rate: <.01 seconds

(per FTMS 101C Method 4046)

Testing

Floor mats should be tested as part of ANSI/ESD S20.20-2007 Compliance Verification testing per ESD TR53. Mats should be tested to ensure that the mats are within spec. Desco manufactures multiple styles of surface resistivity meters for testing floor mats and other surfaces.

Storage

Statguard[®] Floor Mat Cleaner product does not have a set life span. The chemicals are not known to degrade over time when stored at the proper temperature conditions as stated in the Safety Data Sheet. We also recommend that this product be stored in its original container and be sealed when not in use.

RoHS 2, REACH, and Conflict Minerals Statement

None of the RoHS 2 restricted materials or REACH substances of very high concern as of 2014/12/17, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at

DescoIndustries.com.

Limited Warranty, Warranty Exclusions, Limit of Liability and RMA Request Instructions

See Desco Industries Inc. Warranty http://www.descoindustries.com/Warranty.aspx

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Web Site: DescoIndustries.com

© 2015 DESCO INDUSTRIES, INC TB-3057 Page 2 of 6

Safety Data Sheet

May be used to comply with ANSI Z400.1-2004, 29 CFR 1910.1200, Regulation (EC) No 1272/2008 (CLP Regulation) and GHS. Standards must be consulted for specific requirements.

NFPA Designation 704

Degree of Hazard

1 = Slight 4 = Extreme 3 = High 0 = Insignificant

2 = Moderate

Special Hazard

Health

(Blue)

(Red) Instability (Yellow)

Flammability

0

HMIS RATING: Health 1, Flammability 1, Physical Hazard 0, Personal Protection B

SECTION 1 — IDENTIFICATION OF THE PRODUCT and OF THE ENTERPRISE

Product Name: Statguard® Floor Mat Cleaner

Antistatic Mat Cleaner Recommended Use: Desco Industries, Inc. Manufacturer: Address: One Colgate Way.

Canton, MA 02021. 781-821-8370

Telephone: **Emergency Number:** 781-821-8370

SECTION 2 — HAZARDS IDENTIFICATION

Classification:

Flammable liquid	Category 3
Eye irritation	Category 2A-2B

Labelling:

Symbol: Flame, Exclamation mark.

Signal word: Warning.

Hazard statement: Flammable liquid and Eye irritation.

Precautionary statements:

IF SWALLOWED: Immediately call your doctor or physician. Do NOT

induce vomiting.

Do not eat, drink or use with open flame. Wash hands thoroughly after handling.

Keep container tightly closed.

Keep away from heat/sparks/open flame.

Store in cool ventilated place.

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients: CAS No. Weight %

Isopropanol* 67-63-0 5-25%

*These items are listed and subjected to the reporting requirements of the SARA Title III Section 313 Inventory of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR37.

SECTION 4 — FIRST AID MEASURES

Eye Contact: Flush with water for at least 15 minutes.

Skin Contact: Wash with soap and water.

Ingestion: DO NOT induce vomiting. Contact a physician.

Inhalation: Move subject to fresh air.

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Web Site: DescoIndustries.com

© 2015 DESCO INDUSTRIES, INC TB-3057 Page 3 of 6

SECTION 5 — FIRE FIGHTING MEASURES

Proper Extinguishing Media: Water.

Unsuitable Extinguishing Methods: N/A.

Protective Equipment & Precautions: Wearing of appropriate protective equipment and clothing.

Special Fire Fighting Procedures: Cool containers with water.

Unusual Fire and Explosion Hazards: None known.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wearing protective clothing. Inhalation protection. Extinguish all ignition

sources.

Environmental Precautions: Biodegradable.

Clean Up: Contain and collect material into plastic container. Water rinse and drain,

flush small amounts. Use sanitary landfill disposal. Follow state and local

regulations (RCRA; Subtitle D).

SECTION 7 — HANDLING AND STORAGE

Handling: Use in well-ventilated areas; avoid breathing vapors. Keep containers

closed when not in use. Avoid from freezing.

Storage: Storage temperature: Max. 49°C/120°F 1°C/34°F.

Keep from freezing.

SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure Limits

Hazardous Ingredients: CAS No. TLV-value Isopropanol* 67-63-0 400 ppm

Engineering Controls

Control Parameters: TLV-value 400 ppm maximum for Isopropanol.

Measures for Technical Control: Preferences of technical measure to prevent or control contact with the

product. Isolating process and personnel, mechanical ventilation (dilution and local exhaust) and the regulation of process conditions. In case of non-prevention or non-control, a proper protective wearing should be used.

Personal Protection

Respiratory Protection (Specify Type): Wear MSHA/NIOSH approved respirator where exposure limits are

exceeded.

Hand Protection: Impervious/Neoprene Gloves.

Eye Protection: Safety glasses or Chemical splash goggles as defined in ANSI Z-87.1 or a

similar standard.

Work/Hygienic Practices: Wash hands before eating, smoking, or using washroom facilities.

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Web Site: DescoIndustries.com

TB-3057 Page 4 of 6 © 2015 DESCO INDUSTRIES, INC

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid. Colour: Clear violet. Floral Alcohol. Odor: **Boiling Point:** >200°F (93.3°C).

Melting Point: N/A. Specific Gravity ($H_2O = 1$): .98 Solubility in Water:

Complete. pH: 6-8

VOC per Method 24 of EPA: 1% VOC by wt. Flash Point: 106°F (41°C).

Flammability Limits: N/A. (vol. % in air) 18.0 Vapor Pressure (mm Hg): Vapor Density (air=1): Density at 20°C: 1.06 8.17 lbs./gal.

Flammability: Classification according to NFPA and OSHA as "non-flammable",

Flammable Category 3 according to EU and GHS.

Ignition Temperature: N/A. .28 **Evaporation** Rate:

SECTION 10 — STABILITY AND REACTIVITY

Hazardous Decomposition/Byproducts: Thermal decomposition may yield carbon monoxide.

Incompatibility (Materials to Avoid): Strong Oxidizers.

Stability/Reactivity: Stable product at normal conditions.

Conditions to Avoid: Temperatures above 100°F (38°C) and below 34°F (1°C).

Hazardous Polymerization: N/A.

SECTION 11 — TOXICOLOGICAL INFORMATION

All information refers to the main component Isopropanol.

None known. Acute toxicity: Special Effects: None known.

SECTION 12 — ECOLOGICAL INFORMATION

Mobility: The product is aqueous and will be separated in aqueous conditions.

Degradability: N/A.

Bioaccumulation: Not likely.

Ecotoxicity: None known.

Reference to BimSchV: N/A.

Hazard Classification: None hazardous.

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Web Site: DescoIndustries.com

© 2015 DESCO INDUSTRIES, INC TB-3057 Page 5 of 6

SECTION 13 — DISPOSAL CONSIDERATIONS

Product: Contain and collect material into plastic container. Water rinse and drain,

flush small amounts. Use sanitary landfill disposal. Follow state and local

regulations (RCRA; Subtitle D).

SECTION 14 — TRANSPORT INFORMATION

This product is not classified for transport under ADR/IMDG regulations.

SECTION 15 — REGULATORY INFORMATION

Physical/Chemical Indication: Non-flammable (NFPA and OSHA), Flammable (EU and GHS).

Safety Phrase: (S2): keep away from children, (S7): keep containers well closed,

(S24/25): avoid contact with skin and eyes,

(S62): if swallowed, do not induce vomiting; seek medical advice

immediately and show this container or label.

EINECS Status: All components are included in the EINECS inventories.

TSCA: All ingredients of this product are listed or are excluded from the listing on

the U.S. Toxic substance.

REACH: This product does not require REACH registration.

SECTION 16 — OTHER INFORMATION

HMIS RATING: Health 1, Flammability 1, Physical Hazard 0, Personal Protection B

NFPA RATING: Special Hazard: N/A, Health: 1, Flammability: 1, Instability: 0

SDS Updated: 2015-04-09

Disclaimer

OTHER INFORMATION: This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitableness and completeness of such information for his own particular use.

DESCO INDUSTRIES INC. • 3651 Walnut Avenue, Chino, CA 91710 • (909) 627-8178 • Web Site: DescoIndustries.com

TB-3057 Page 6 of 6 © 2015 DESCO INDUSTRIES, INC.