



E002

E003

E004

E005

E002 | EXPERIMENTAL BOARD DOT GRID

Experimental board in euro measurement, flash-gold plated (better for soldering „leadfree“).

Technical Data:

One-side copper layer: approx. 35 µm | **Material:** FR2 (Pertinax) | **Hole distance:** 2,54 mm | **Diameter of holes:** Ø approx. 1 mm | **Thickness:** approx. 1,5 mm | **Dimensions:** approx. 100 x 160 mm | Round lands for soldering

E003 | EXPERIMENTAL BOARD STRIP GRID

Experimental board in euro measurement, flash-gold plated (better for soldering „lead free“).

Technical Data:

One-side copper layer: approx. 35 µm | **Material:** FR2 (Pertinax) | **Hole distance:** 2,54 mm | **Diameter of holes:** Ø approx. 1 mm | **Thickness:** approx. 1,5 mm | **Dimensions:** approx. 100 x 160 mm

E004 | EXPERIMENTAL BOARD DOT GRID

Experimental board in euro measurement, flash-gold plated (better for soldering „leadfree“).

Technical Data:

One-side copper layer: approx. 35 µm | **Material:** FR4 (Epoxid) | **Hole distance:** 2,54 mm | **Diameter of holes:** Ø approx. 1 mm | **Thickness:** approx. 1,5 mm | **Dimensions:** approx. 100 x 160 mm

E005 | EXPERIMENTAL BOARD STRIP GRID

Experimental board in euro measurement, flash-gold plated (better for soldering „leadfree“).

Technical Data:

One-side copper layer: approx. 35 µm | **Material:** FR4 (Epoxid) | **Hole distance:** 2,54 mm | **Diameter of holes:** Ø approx. 1 mm | **Thickness:** approx. 1,5 mm | **Dimensions:** approx. 100 x 160 mm