

## T50RDH0UVC2

Article Number: 117-05011

Double Head Tie, 8.3" Long, 50lb Tensile Strength, PA66UV, Black, 100/pkg



Download drawing



Download spec sheet

### Base Data

**Local Order Number** T50RDH0UVC2

**Type** T50RDH

**Color** Black (BK)

- Features and Benefits**
- UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures.
  - The tie contains a dual locking design to secure two bundles at once.
  - Head design can also provide spacing between parallel bundles.
  - Bent tail allows for quick insertion into head.

**Product Description** The double head cable tie was designed with a dual locking head to secure two bundles simultaneously. The head also provides separation between bundles or bundles running parallel to each other. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Double Head Tie, 8.3" Long, 50lb Tensile Strength, PA66UV, Black, 100/pkg

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225.0 N

**Length L (Imperial)** 8.3 "

**Length L (Metric)** 210.0 mm

**Bundle Diameter 2nd Loop Max. (Imperial)** 0.75 "

**Fixation Method**None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.19 "

**Width W (Metric)** 4.7 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.6 mm

**Bundle Diameter Max. (Imperial)** 2.0 "

**Bundle Diameter Max. (Metric)** 50.0 mm

**Bundle Diameter 1st Loop Max. (Imperial)** 1.7 "

**Bundle Diameter 1st Loop Max. (Metric)**44.4 mm

**Thickness T (Imperial)** 0.055 "

**Cable Tie Head Length (Imperial)** 0.53 "

**Cable Tie Head Width (Imperial)** 0.32 "

**Bundle Diameter 2nd Loop Max. (Metric)** 19.0 mm

**Thickness T (Metric)** 1.4 mm

## Logistics and Packaging

---

**Quantity Per** bag

**Package Quantity (Metric)** 100

**Carton Quantity** 5000

## Material and Specifications

---

**Material** Polyamide 6.6 UV-stabilized (PA66UV)

**Material Shortcut** PA66UV

**Flammability** UL94 V2

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**Certification/Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** No